

Spacer - DP-PT 10,3-HESI - 3062155


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Spacer for adjacent fuse carriers, 4 should be inserted (2 should be inserted on the outer ends of the fuse terminal block)



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	200 pc
GTIN	 4 055626 056883
GTIN	4055626056883
Custom tariff number	39269097
Country of origin	China

Technical data

General

Color	white
Material	PA
Flammability rating according to UL 94	V0

Dimensions

Width	4.4 mm
Length	21.1 mm
Diameter	25 mm
Pitch	4.4 mm

Ambient conditions

Operating temperature	-60 °C ... 85 °C
-----------------------	------------------

Spacer - DP-PT 10,3-HESI - 3062155

Technical data

Ambient conditions

Ambient temperature (storage/transport)	-25 °C ... 55 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Permissible humidity (storage/transport)	30 % ... 70 %
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 10.0.1	27141190
eCl@ss 11.0	27141190
eCl@ss 4.0	21011300
eCl@ss 4.1	21011300
eCl@ss 5.0	27141100
eCl@ss 5.1	27141100
eCl@ss 6.0	27141100
eCl@ss 7.0	27141133
eCl@ss 9.0	27141133

ETIM

ETIM 6.0	EC000886
ETIM 7.0	EC000886

UNSPSC

UNSPSC 13.2	39121425
UNSPSC 18.0	39121425
UNSPSC 19.0	39121425
UNSPSC 20.0	39121425
UNSPSC 21.0	39121425