

https://www.phoenixcontact.com/us/products/1002665



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Comfort device adapter with CrossLink® interface and moveable DIN rail, rated current: 25 A

Your advantages

- · Cable ends ultrasound-compressed
- · Snap-on mechanism for quick and easy attachment to the CrossPowerSystem power distribution board

Commercial data

Item number	1002665
Packing unit	4 pc
Minimum order quantity	4 pc
Sales key	C470
Product key	CK7852
Catalog page	Page 53 (C-5-2019)
GTIN	4055626468143
Weight per piece (including packing)	131 g
Weight per piece (excluding packing)	127 g
Customs tariff number	85369095
Country of origin	DE



https://www.phoenixcontact.com/us/products/1002665



Technical data

Product properties

Product type	Adapter
Product family	CrossPowerSystem
Application	Device adapter

Electrical properties

Rated voltage	690 V AC (IEC)
	600 V AC (UL)
Rated current	25 A (IEC)
	20 A (UL)
Rated surge voltage	6 kV

Dimensions

Width	45 mm
Height	160 mm
Depth	45 mm



https://www.phoenixcontact.com/us/products/1002665



Classifications

UNSPSC 21.0

ECLASS

	ECLASS-11.0	27371392
	ECLASS-13.0	27371392
	ECLASS-12.0	27371392
ETIM		
	ETIM 9.0	EC002498
UNSPSC		

39121100



https://www.phoenixcontact.com/us/products/1002665



Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com