

AP-NLS N - Cover profile



1013634

<https://www.phoenixcontact.com/us/products/1013634>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cover profile, height: 300 mm, color: transparent

Commercial data

Item number	1013634
Packing unit	10 pc
Minimum order quantity	10 pc
Product key	BE2ZWX
GTIN	4055626492094
Weight per piece (including packing)	9.941 g
Weight per piece (excluding packing)	9.941 g
Country of origin	DE

AP-NLS N - Cover profile



1013634

<https://www.phoenixcontact.com/us/products/1013634>

Technical data

Notes

General	for neutral busbar
---------	--------------------

Product properties

Product type	Cover profile
--------------	---------------

Dimensions

Height	300 mm
--------	--------

Material specifications

Color	transparent
Flammability rating according to UL 94	V0

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-60 °C ... 85 °C
Ambient temperature (storage/transport)	-25 °C ... 55 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (storage/transport)	30 % ... 70 %

AP-NLS N - Cover profile



1013634

<https://www.phoenixcontact.com/us/products/1013634>

Classifications

ECLASS

ECLASS-11.0	27141190
ECLASS-13.0	27141190
ECLASS-12.0	27141190

ETIM

ETIM 9.0	EC002848
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

AP-NLS N - Cover profile



1013634

<https://www.phoenixcontact.com/us/products/1013634>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e No hazardous substances above threshold values
------------	---

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com