

https://www.phoenixcontact.com/us/products/1003289



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Comfort device adapter with CrossLink® interface and moveable DIN rail, rated current: 45 A

Your advantages

- · Cable ends ultrasound-compressed
- · Snap-on mechanism for quick and easy attachment to the CrossPowerSystem power distribution board

Commercial data

Item number	1003289
Packing unit	4 pc
Minimum order quantity	4 pc
Sales key	C470
Product key	CK7854
Catalog page	Page 53 (C-5-2019)
GTIN	4055626470740
Weight per piece (including packing)	167.375 g
Weight per piece (excluding packing)	167.375 g
Customs tariff number	85369095
Country of origin	DE



https://www.phoenixcontact.com/us/products/1003289



Technical data

Product properties

Product type	Adapter
Product family	CrossPowerSystem
Application	Device adapter

Electrical properties

Rated voltage	690 V AC (IEC)
	600 V AC (UL)
Rated current	45 A (IEC)
	40 A (UL)
Rated surge voltage	6 kV

Dimensions

Width	45 mm
Height	160 mm
Depth	45 mm



https://www.phoenixcontact.com/us/products/1003289



Classifications

ECLASS

ECLASS-11.0	27371392
ECLASS-13.0	27371392
ECLASS-12.0	27371392
ETIM	
ETIM 9.0	EC002498
LINEDCO	

UNSPSC



https://www.phoenixcontact.com/us/products/1003289



Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com