

AGK PT 4X6/M12 - Pick-off terminal block



1017454

<https://www.phoenixcontact.com/us/products/1017454>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Pick-off terminal block, nom. voltage: 1000 V, nominal current: 41 A, number of connections: 5, connection method: Push-in connection, 1 level, Rated cross section: 6 mm², cross section: 0.5 mm² - 10 mm², Bolt connection, 1 level, mounting type: on base element, color: gray

Your advantages

- The fully insulated, optionally used pick-off terminal block enables voltage pick-off
- Large-surface marking

Commercial data

Item number	1017454
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	BE29
Product key	BE2ZWX
Catalog page	Page 119 (C-1-2019)
GTIN	4055626500645
Weight per piece (including packing)	42.3 g
Weight per piece (excluding packing)	37.7 g
Customs tariff number	85369010
Country of origin	CN

AGK PT 4X6/M12 - Pick-off terminal block



1017454

<https://www.phoenixcontact.com/us/products/1017454>

Technical data

Product properties

Product type	Pick-off terminal
Number of connections	5
Number of rows	1
Potentials	1

Insulation characteristics

Overvoltage category	III
----------------------	-----

Electrical properties

Rated surge voltage	8 kV
Maximum power dissipation for nominal condition	1.31 W

Connection data

Number of connections per level	5
Nominal cross section	6 mm ²
Rated cross section AWG	10

1 level

Stripping length	10 mm ... 12 mm
Internal cylindrical gage	A5
Connection in acc. with standard	IEC 60947-7-1
Conductor cross section rigid	0.5 mm ² ... 10 mm ²
Cross section AWG	20 ... 8 (converted acc. to IEC)
Conductor cross section flexible	0.5 mm ² ... 6 mm ²
Conductor cross section, flexible [AWG]	20 ... 10 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve)	0.5 mm ² ... 6 mm ²
Flexible conductor cross section (ferrule with plastic sleeve)	0.5 mm ² ... 6 mm ²
Conductor cross-section flexible (2 conductors with the same cross-section, with TWIN ferrule and plastic sleeve)	0.5 mm ² ... 1.5 mm ²
Nominal current	41 A
Maximum load current	57 A
Maximum total current	109 A (Bolt connection)
Nominal voltage	1000 V
Nominal cross section	6 mm ²

1 level

Screw thread	M12
Note	Connection bolts
Tightening torque	14 ... 31 Nm
Connection in acc. with standard	IEC 60947-7-1
Conductor cross section flexible	6 mm ² ... 120 mm ²
Conductor cross section, flexible [AWG]	10 ... 250 kcmil (converted acc. to IEC)

AGK PT 4X6/M12 - Pick-off terminal block



1017454

<https://www.phoenixcontact.com/us/products/1017454>

Nominal current	41 A
-----------------	------

Cable lug connection

Cross section range AWG	(converted acc. to IEC)
Hole diameter	12.4 mm
Width	32 mm
Bolt diameter	12 mm
Screw thread	M12

Dimensions

Width	31 mm
Height	57.4 mm
Depth	32.3 mm
Hole diameter	12.4 mm

Material specifications

Color	gray
Flammability rating according to UL 94	V0
Insulating material group	I
Insulating material	PA

Mechanical properties

Mechanical data

Open side panel	No
-----------------	----

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (operation)	20 % ... 90 %
Permissible humidity (storage/transport)	30 % ... 70 %

Standards and regulations

Connection in acc. with standard	IEC 60947-7-1
	IEC 60947-7-1

Mounting

Mounting type	on base element
---------------	-----------------

AGK PT 4X6/M12 - Pick-off terminal block



1017454

<https://www.phoenixcontact.com/us/products/1017454>

Classifications

ECLASS

ECLASS-11.0	27141120
ECLASS-13.0	27250308

ETIM

ETIM 9.0	EC000897
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

AGK PT 4X6/M12 - Pick-off terminal block



1017454

<https://www.phoenixcontact.com/us/products/1017454>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e No hazardous substances above threshold values
------------	---

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com