

HC-M-08-EMC-DSUB-M - Connector



1066082

<https://www.phoenixcontact.com/us/products/1066082>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Connector, number of positions: 8, power contacts: 0, control contacts: 8, Pin, Crimp connection, 48 V, 5 A, 0.09 mm² ... 0.52 mm², external cable diameter:3 mm ... 9.5 mm, application: Data/signal

Commercial data

Item number	1066082
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF62
Product key	BF7ACB
Catalog page	Page 583 (C-2-2019)
GTIN	4055626728889
Weight per piece (including packing)	31.976 g
Weight per piece (excluding packing)	31.976 g
Customs tariff number	85389099
Country of origin	CN

HC-M-08-EMC-DSUB-M - Connector

1066082

<https://www.phoenixcontact.com/us/products/1066082>



Technical data

Notes

General	Order crimp contacts CUC-DSC-C1BAU-S/DSC... separately
General	The potential of the EMC connector housing is isolated from the potential of the heavy connector.
General	Clamps for the clamping range of 3 mm - 6 mm and 6 mm - 9.5 mm
General	Can be used in Item No.: 1417374 HC-M-02-EMC-M

Product properties

Product type	EMC insert, modular
Number of positions	8
Connection profile	8
Contact numbering	1 - 8
Application	Data/signal
No. of power contacts	0
No. of control contacts	8
Contact material type	turned
Series	HC-M-EMV
Shielded	yes

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Electrical properties

Rated voltage (III/3)	48 V
Rated surge voltage	0.8 kV
Rated current	5 A

Connection data

Connection technology

Connection technology	Crimp connection
-----------------------	------------------

Conductor connection

Conductor cross section	0.09 mm² ... 0.52 mm²
Connection cross section AWG	28 ... 20

Dimensions

Dimensional drawing	
---------------------	--

HC-M-08-EMC-DSUB-M - Connector



1066082

<https://www.phoenixcontact.com/us/products/1066082>

Height	15.5 mm
Length	46.2 mm

Mechanical characteristics

Contact diameter	1 mm
------------------	------

Material specifications

Material Line conductor	Zinc alloy
Flammability rating according to UL 94	V0
Contact material	Copper alloy
Contact surface material	Au
Contact carrier material	PC

Cable/line

External cable diameter ()	3 mm ... 9.5 mm
-----------------------------	-----------------

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 500
-----------------------------	-------

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
---------------------------------	------------------

Mounting

Assembly instructions	The round contact carrier can be separated in the middle for the purpose of assembling/disassembling contacts. Disassemble the connector from the plastic module using the tool, order no.: 1678635 HC-M-EMV-KON-EWZ
-----------------------	--

HC-M-08-EMC-DSUB-M - Connector



1066082

<https://www.phoenixcontact.com/us/products/1066082>

Classifications

ECLASS

ECLASS-11.0	27440205
ECLASS-12.0	27440205
ECLASS-13.0	27440205

ETIM

ETIM 9.0	EC000438
----------	----------

UNSPSC

UNSPSC 21.0	39121500
-------------	----------

HC-M-08-EMC-DSUB-M - Connector



1066082

<https://www.phoenixcontact.com/us/products/1066082>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com