

# CSD-SL 300 GN 30X30 - Signal light



1051088

<https://www.phoenixcontact.com/us/products/1051088>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Signal light, 24 V DC, IALA green, optimum, emission angle (vertical/Horizontal): 30 °/30 °, diameter: 272 mm, degree of protection: IP65/IP67, Communication interface

## Product description

The signal lights for maritime use can be used for the reliable and energy-efficient operation of light-signal systems, such as locks. Only components that conform to the industry standard are used for the monitoring functions. The signal light 300 is available in various light colors in accordance with major standards (e.g. IALA recommendation E200-1 and CIE 1931). The fieldbus communication provides the user with a large amount of diagnostic and status information.

## Your advantages

- Developed in accordance with EN 12966-1, IALA recommendation E200-1, and CIE 1931
- Failsafe function
- 400 m connection to the control unit via fieldbus
- Diagnostic capability
- High light and color intensity
- Application-specific programming supported
- Particularly economical thanks to energy-efficient LED technology and an LED service life of at least 50 000 h
- Emission angle: 30° x 30°
- Durable and energy-saving LED technology
- Fieldbus communication

## Commercial data

Item number	1051088
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	DRL122
Catalog page	Page 513 (C-6-2019)
GTIN	4055626670638
Weight per piece (including packing)	4,200 g
Weight per piece (excluding packing)	3,860 g
Country of origin	DE

# CSD-SL 300 GN 30X30 - Signal light



1051088

<https://www.phoenixcontact.com/us/products/1051088>

## Technical data

### Product properties

Product type	Signaling light
Application	Maritime navigation
	Transportation infrastructure
Design	Operating hours counter
Special properties	Communication interface
Diagnostics messages	LEDs; temperature, current, voltage, etc. yes
	Mains failure, communication failure Failsafe
Light color	IALA green, optimum

### Electrical properties

#### General

Inrush current	max. 36 A ( $\mu$ -sec-pulse)
----------------	-------------------------------

#### Supply: Module electronics

Connection method	M17 hybrid connectors with SPEEDCON locking system
Number of positions	8
Supply voltage	24 V DC (DC)
Current consumption	max. 2.73 A (green LEDs)
Power consumption	max. 75 W (green LEDs)

### Connection data

Connection method	M17 hybrid connectors with SPEEDCON locking system
-------------------	--

### Signaling

#### Light properties

Source of light type	LED
Number of LEDs	30 (in accordance with IALA recommendation E200-1 and CIE 1931)
Service life, lighting appliance	50000 h
Light color	IALA green, optimum
Color temperature	490...510 nm
Color class	C3 (EN 12966)
Luminance	L3 (EN 12966)
Luminous intensity	6800 Cd
Can be dimmed	Yes, in 256 steps
Emission angle	30 °
	30 °
Luminance ratio	R3 (EN 12966)
Phantom light class	5 (EN 12368)

#### Diagnostic messages

# CSD-SL 300 GN 30X30 - Signal light



1051088

<https://www.phoenixcontact.com/us/products/1051088>

Diagnostics	LEDs; temperature, current, voltage, etc.
Message	yes

## Diagnostic messages

Diagnostics	Mains failure, communication failure
Message	Failsafe

## Dimensions

Depth	68 mm
Diameter	272 mm

## Material specifications

Color	black (RAL 9005)
Material	Aluminum die-cast in accordance with DIN EN 1706
	Glass

## Environmental and real-life conditions

### Ambient conditions

Ambient temperature (operation)	-25 °C ... 55 °C
Degree of protection	IP65/IP67 (When installed)
Air pressure (operation)	70 hPa ... 106 kPa (up to 3000 m above sea level)
Air pressure (storage/transport)	70 hPa ... 106 kPa (up to 3000 m above sea level)
Ambient temperature (storage/transport)	-25 °C ... 85 °C

## Mounting

Mounting type	Screw mounting
Assembly instructions	Use of stainless steel fittings (corrosion-resistant)

# CSD-SL 300 GN 30X30 - Signal light



1051088

<https://www.phoenixcontact.com/us/products/1051088>

## Classifications

### ECLASS

ECLASS-11.0	27110201
ECLASS-13.0	27110201
ECLASS-12.0	27110201

### ETIM

ETIM 9.0	EC002750
----------	----------

### UNSPSC

UNSPSC 21.0	39111800
-------------	----------

# CSD-SL 300 GN 30X30 - Signal light



1051088

<https://www.phoenixcontact.com/us/products/1051088>

## Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)