

1043501

https://www.phoenixcontact.com/us/products/1043501

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Program and configuration memory for storing the application programs and other files in the file system of the PLC, plug-in, 2 GB.

### Your advantages

- · For storing application programs and other files in the file system of the PLC
- Program and configuration memory

### Commercial data

| Item number                          | 1043501            |
|--------------------------------------|--------------------|
| Packing unit                         | 1 pc               |
| Minimum order quantity               | 1 pc               |
| Sales key                            | DR09               |
| Product key                          | DRADZA             |
| Catalog page                         | Page 10 (C-6-2019) |
| GTIN                                 | 4055626607573      |
| Weight per piece (including packing) | 9.8 g              |
| Weight per piece (excluding packing) | 8.5 g              |
| Customs tariff number                | 85235190           |
| Country of origin                    | DE                 |



1043501

https://www.phoenixcontact.com/us/products/1043501

## Technical data

#### Product properties

| Product type                                    | Storage medium               |
|---|------------------------------|
| Mounting position                               | vertical                     |
| Application                                     | Program/configuration memory |
| Electrical properties                           |                              |
| Maximum power dissipation for nominal condition | 0.165 W                      |
| Supply  |                              |
| Supply voltage                                  | 3.3 V DC                     |
| Supply voltage range                            | 2.7 V DC 3.6 V DC            |
| Typical current consumption                     | typ. 50 mA                   |
| Material specifications                         |                              |
| Housing material                                | Plastic                      |
| Environmental and real-life conditions          |                              |
| Ambient conditions                              | (0.10, 05.10)                |
| Ambient temperature (operation)                 | -40 °C 85 °C                 |
| Mounting  |                              |
| Mounting position                               | vertical                     |
|   |                              |



1043501

https://www.phoenixcontact.com/us/products/1043501

## Classifications

#### ECLASS

|        | ECLASS-11.0 | 27242212 |  |
|--------|-------------|----------|--|
|        | ECLASS-13.0 | 27242212 |  |
|        | ECLASS-12.0 | 27242212 |  |
| ETIM   |             |          |  |
|        | ETIM 9.0    | EC000192 |  |
| UNSPSC |             |          |  |
|        | UNSPSC 21.0 | 32101600 |  |



1043501

https://www.phoenixcontact.com/us/products/1043501

### Environmental product compliance

China RoHS

Environmentally friendly use period: unlimited = EFUP-e No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com