PLC-LOGIC-KIT-BM2 - Set

1064629

https://www.phoenixcontact.com/us/products/1064629

PLC logic set consisting of: plug-in basic logic module (BM2) and eight relay terminal blocks with Push-in connection (1 changeover contact, 250 V AC/DC, max.6 A)

Commercial data

Item number	1064629
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	CK26Z2
GTIN	4055626722726
Weight per piece (including packing)	619.1 g
Weight per piece (excluding packing)	544 g
Country of origin	DE

PLC-LOGIC-KIT-BM2 - Set

1064629

https://www.phoenixcontact.com/us/products/1064629

Set consists of

PLC-V8C/PT-24DC/BM2 - Controller

2907446

https://www.phoenixcontact.com/us/products/2907446

PLC logic basic module, Generation 2, with 16 I/Os, for plug-in connection to eight digital or analog PLC-INTERFACE terminal blocks, can be extended to 48 I/Os, real-time clock, micro USB female connector, accommodates memory module and Bluetooth adapter, Push-in connection

PLC-RPT- 24DC/21 - Relay Module

2900299

https://www.phoenixcontact.com/us/products/2900299

PLC-INTERFACE, consisting of PLC-BPT.../21 basic terminal block with Push-in connection and plug-in miniature relay with power contact, for mounting on NS 35/7,5 DIN rail, 1 changeover contact, input voltage 24 V DC

PLC-LOGIC-KIT-BM2 - Set

Technical data

Notes

General	For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.

Product properties

Product type	Starter kit

Mounting

Mounting type	DIN rail mounting

PLC-LOGIC-KIT-BM2 - Set

1064629

https://www.phoenixcontact.com/us/products/1064629

Classifications

ECLASS

ECLASS-12.0	27242219
ECLASS-13.0	27242219
ECLASS-11.0	27242219

ETIM

ETIM 9.0	EC002581

UNSPSC

UNSPSC 21.0	32151700

PLC-LOGIC-KIT-BM2 - Set

Environmental product compliance

REACh SVHC	Lead 7439-92-1
	Hexahydromethylphthalic anhydride

China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"