

VAL-MS 1500DC-PV/2+V - Type 2 surge arrester



1033708

<https://www.phoenixcontact.com/us/products/1033708>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Surge protective device for 2-pos. isolated and grounded 1500 V DC PV systems, for DIN rail mounting, 3-pos. base element, three pluggable temperature-monitored protective elements, status message on each plug.

Your advantages

- Quality proven millions of times over in the widest range of applications
- Rapid installation with bridges, thanks to industry-standard overall width of 1 HP
- Easy testing and insulation measurement, thanks to pluggable protection modules
- Wide range of applications due to various nominal voltages
- High degree of modularity provides individual solutions for every application

Commercial data

Item number	1033708
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	CL01
Product key	CL1324
Catalog page	Page 73 (C-4-2019)
GTIN	4055626540351
Weight per piece (including packing)	351.1 g
Weight per piece (excluding packing)	335.3 g
Customs tariff number	85354000
Country of origin	DE

VAL-MS 1500DC-PV/2+V - Type 2 surge arrester



1033708

<https://www.phoenixcontact.com/us/products/1033708>

Technical data

Notes

General

Note	The device is intended for touch proof installation in a housing. Ensure that there is a gap of at least 8 mm between the active and grounded parts in the connection area.
------	---

Product properties

IEC test classification	PV II
	PV T2
EN type	T2
IEC power supply system	DC
Type	DIN rail module, two-section, divisible
Distance between live and grounded parts	8 mm
Product type	PV arrester
Product family	VALVETRAB MS
Installation location	Interior
Installation location of the disconnect device	Internal
Accessibility	Accessible
Connection configuration	Y configuration
SPD failure behavior	OCFM (Open-Circuit Failure Mode)
Surge protection fault message	optical

Insulation characteristics

Overvoltage category	III
Pollution degree	2

Connection data

Connection method	Screw connection
Screw thread	M5
Tightening torque	3 Nm (1.5 mm ² ... 16 mm ²)
	4.5 Nm (25 mm ² ... 35 mm ²)
Stripping length	16 mm
Conductor cross section flexible	1.5 mm ² ... 25 mm ²
Conductor cross section rigid	1.5 mm ² ... 35 mm ²
Conductor cross section AWG	15 ... 2
Connection method	Fork-type cable lug
Conductor cross section flexible	1.5 mm ² ... 16 mm ²


Dimensions

VAL-MS 1500DC-PV/2+V - Type 2 surge arrester



1033708

<https://www.phoenixcontact.com/us/products/1033708>

Dimensional drawing	
Width	53.4 mm
Height	89.8 mm
Depth	65.7 mm
Horizontal pitch	3 Div.

Material specifications

Color	black (RAL 9005)
Flammability rating according to UL 94	V-0
CTI value of material	600
Insulating material	PA 6.6-FR PBT-FR
Material group	I
Housing material	PA 6.6-FR PBT-FR

Mechanical properties

Mechanical data

Open side panel	No
-----------------	----

Protective circuit

Mode of protection	(L+) - (L-) (L+) - PE (L-) - PE
Direction of action	(L+)-PE & (L-)-PE & (L+)-(L-)
Rated load current I_L	80 A
Residual current I_{PE}	$\leq 350 \mu\text{A DC}$ $\leq 600 \mu\text{A AC}$
Standby power consumption P_C	$\leq 250.00 \text{ mVA}$
Nominal discharge current $I_n (8/20) \mu\text{s}$	15 kA
Maximum discharge current $I_{max} (8/20) \mu\text{s}$	30 kA
Total discharge current $I_{total} (8/20) \mu\text{s}$	30 kA
Voltage protection level U_p	$\leq 5 \text{ kV}$
Residual voltage U_{res}	$\leq 3.8 \text{ kV (at 3 kA)}$ $\leq 4.1 \text{ kV (at 5 kA)}$ $\leq 4.4 \text{ kV (at 10 kA)}$ $\leq 5 \text{ kV (at 15 kA)}$ $\leq 5.3 \text{ kV (at 20 kA)}$ $\leq 5.7 \text{ kV (at 30 kA)}$ $\leq 6 \text{ kV (at 40 kA)}$

VAL-MS 1500DC-PV/2+V - Type 2 surge arrester



1033708

<https://www.phoenixcontact.com/us/products/1033708>

Response time t_A	≤ 25 ns
---------------------	--------------

PV protective circuit

Connection configuration	Y configuration
SPD failure behavior	OCFM (Open-Circuit Failure Mode)

Protective circuit DC voltage side (DC)

Open circuit voltage U_{OCSTC}	≤ 1250 V DC
Maximum discharge current I_{max} (8/20) μ s	30 kA
Response time t_A	≤ 25 ns
Total discharge current I_{total} (8/20) μ s	30 kA
Nominal discharge current I_n (8/20) μ s	15 kA
Rated load current I_L	80 A
Continuous operating current I_{CPV}	< 350 μ A
Maximum continuous operating voltage U_{CPV}	1500 V DC
Short-circuit current rating I_{SCPV}	2000 A
Residual voltage U_{res}	≤ 3.8 kV (at 3 kA) ≤ 4.1 kV (at 5 kA) ≤ 4.4 kV (at 10 kA) ≤ 5 kV (at 15 kA) ≤ 5.3 kV (at 20 kA) ≤ 5.7 kV (at 30 kA) ≤ 6 kV (at 40 kA)
Residual current I_{PE}	≤ 350 μ A DC ≤ 600 μ A AC
Voltage protection level U_p	≤ 5 kV
Standby power consumption P_C	≤ 250.00 mVA

Additional technical data

Maximum discharge current I_{max} (8/20) μ s	40 kA
Nominal discharge current I_n (8/20) μ s	20 kA (4x (5x I_n 120 s) 30 min))

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20 (only when all terminal points are used)
Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Altitude	≤ 3000 m (amsl)
Permissible humidity (operation)	5 % ... 95 %
Shock (operation)	30g (Half-sine / 11 ms / 3x \pm X, \pm Y, \pm Z)
Vibration (operation)	5g (5-500 Hz/2.5 h/XYZ)

Approvals

UL specifications

VAL-MS 1500DC-PV/2+V - Type 2 surge arrester



1033708

<https://www.phoenixcontact.com/us/products/1033708>

Maximum continuous operating voltage MCOV	1500 V DC
Short-circuit current rating (SCCR)	50 kA
Voltage protection rating VPR	4 kV
Nominal discharge current I_n	10 kA
Mode of protection	(DC+) - (DC-) (DC+) - G (DC-) - G
Nominal voltage	1500 V DC
Power distribution system	DC PV
SPD Type	1CA

UL connection data

Tightening torque	30 lb _F -in.
Conductor cross section AWG	14 ... 2

Standards and regulations

Standards/specifications	EN 61643-31
Note	2019
Standards/specifications	IEC 61643-31
Note	2018

Mounting

Mounting type	DIN rail: 35 mm
---------------	-----------------

VAL-MS 1500DC-PV/2+V - Type 2 surge arrester



1033708

<https://www.phoenixcontact.com/us/products/1033708>

Classifications

ECLASS

ECLASS-11.0	27130805
ECLASS-13.0	27171402

ETIM

ETIM 9.0	EC000941
----------	----------

UNSPSC

UNSPSC 21.0	39121620
-------------	----------

VAL-MS 1500DC-PV/2+V - Type 2 surge arrester



1033708

<https://www.phoenixcontact.com/us/products/1033708>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com