

EV-CC-AC1-M3-CBC-SER-HS-MSTB - AC charging controller



1081341

<https://www.phoenixcontact.com/us/products/1081341>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



The EV-CC-AC1-M3-CBC-SER-HS-MSTB charging controller with housing for DIN rail mounting and plug-in connection technology is used to charge electric vehicles on the 3-phase AC power grid in accordance with IEC 61851-1, mode 3. All charging functions, comprehensive configuration settings, and a locking control are already integrated.

Commercial data

Item number	1081341
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	XWBBAA
Catalog page	Page 62 (C-7-2019)
GTIN	4055626809410
Weight per piece (including packing)	397 g
Weight per piece (excluding packing)	382 g
Country of origin	DE

EV-CC-AC1-M3-CBC-SER-HS-MSTB - AC charging controller



1081341

<https://www.phoenixcontact.com/us/products/1081341>

Technical data

Product properties

Product type	AC charging controller
Product family	CHARX control basic
Application	AC charging controller for private and commercial applications (EU/CN)
Operating mode	Stand-Alone
Charging mode	Mode 3, Case B + C

System properties

Charging controllers

Number of charging points	1
---------------------------	---

Electrical properties

Type of charging current	AC
Note on the connection method	with MSTB connection
Locking release in the event of mains failure	Integrated release function of the locking actuator for disconnection of Infrastructure Plug and Infrastructure Socket Outlet

Supply

Supply voltage	230 V
Supply voltage range	100 V AC ... 240 V AC (nominal voltage range)
Max. current consumption	40 mA
Nominal power consumption	< 1 W (No-load)
Frequency range	50 Hz ... 60 Hz

Input data

Digital

Number of digital inputs	5
Frequency range	50 Hz ... 60 Hz
Nominal power consumption	< 0.5 W (No-load)
Nominal current I_N	≤ 1 mA
Nominal input voltage U_N	12 V
Input voltage range U_1	0 V ... 3 V (Off)
Input voltage range U_2	9 V ... 15 V (On)

Output data

Digital

Output name	4 digital outputs
Connection technology	Push-in connection
Maximum output voltage	30 V

EV-CC-AC1-M3-CBC-SER-HS-MSTB - AC charging controller



1081341

<https://www.phoenixcontact.com/us/products/1081341>

Maximum output current	0.5 A (Total current for all outputs; internally supplied)
	0.6 A (Per output; externally supplied)

Switching

Output name	Relay output C _{1,2}
Minimum switching capacity	1500 VA
Maximum switching voltage	250 V AC (External supply)
Max. switching current	6 A

Switching

Output name	Relay output LO+/-
Minimum switching capacity	24 VA
Maximum switching voltage	12 V (Internal supply)
Max. switching current	2 A

Connection data

Conductor connection

Connection method	Pluggable spring-cage terminal blocks
Conductor cross section rigid	0.2 mm ² ... 1.5 mm ²
Conductor cross section flexible	0.2 mm ² ... 1.5 mm ²
Conductor cross section AWG	24 ... 16

Interfaces

Interface	RS-485
-----------	--------

RS-485

Interface	RS-485 2-wire
Bus system	RS-485
Connection method	Pluggable spring-cage terminal blocks
Number of interfaces	1
Transmission speed	9.6 kbps (Standard)
Transmission speed range	9.6 kbps ... 19.2 kbps (adjustable)
Data flow control/protocols	Modbus/RTU (slave)

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-35 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Permissible humidity (operation)	30 % ... 95 %

Approvals

Conformity/Approvals

Conformance	CE-compliant
-------------	--------------

EV-CC-AC1-M3-CBC-SER-HS-MSTB - AC charging controller



1081341

<https://www.phoenixcontact.com/us/products/1081341>

Standards and regulations

Standards

Standards/regulations	IEC 61851-1
-----------------------	-------------

Mounting

Mounting type	DIN rail mounting
Mounting position	any

EV-CC-AC1-M3-CBC-SER-HS-MSTB - AC charging controller



1081341

<https://www.phoenixcontact.com/us/products/1081341>

Classifications

ECLASS

ECLASS-11.0	27144703
ECLASS-12.0	27144703
ECLASS-13.0	27144703

ETIM

ETIM 9.0	EC002889
----------	----------

UNSPSC

UNSPSC 21.0	39121800
-------------	----------

EV-CC-AC1-M3-CBC-SER-HS-MSTB - AC charging controller



1081341

<https://www.phoenixcontact.com/us/products/1081341>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com