

G-ESIS-M12-S68N-PEPDS-BK - Cable gland



1424465

<https://www.phoenixcontact.com/us/products/1424465>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable gland, material for screw connection: PA, application: Ex, external cable diameter 3 mm ... 6 mm, shielding: no, connecting thread: M12 x 1.5, color: jet black RAL 9005, with flat gasket

Product description

Cable gland, with flat gasket

Your advantages

- Glow-wire test: 750°C
- Weatherproof sealing material
- Halogen-free

Commercial data

Item number	1424465
Packing unit	10 pc
Minimum order quantity	10 pc
Product key	BF7DDX
GTIN	4055626375557
Weight per piece (including packing)	8.11 g
Weight per piece (excluding packing)	8.11 g
Country of origin	DE

G-ESIS-M12-S68N-PEPDS-BK - Cable gland



1424465

<https://www.phoenixcontact.com/us/products/1424465>

Technical data


Product properties

Product type	Full screw connection
Application	Ex
No. of conductors	1
Manufacturer	WISKA
Manufacturer Designation	ESKE/1-e 12
Shielded	no

Ex data

Cable types that can be used	for unarmored cables
Suited for EX-applications	yes

Dimensions

Dimensional drawing	
Length	28 mm
Length of the connecting thread	9 mm
Hole diameter	12.1 mm ... 12.3 mm
Wrench size, union nut	16 mm
Wrench size, support	16 mm
Hexagon angular dimension	18 mm
Thread type connection side	M12 x 1.5
Thread pitch	1.5 mm

Connection data

Tightening torque	2 Nm (Support sleeve)
-------------------	-----------------------

Material specifications

Color	black (RAL 9005)
Material Screw connection	PA
Seal material Flat gasket	EPDM
Glow wire ignition temperature GWIT according to EN 60695-2-13	750
Material for screw connection	PA

Cable/line

External cable diameter ()	3 mm ... 6 mm
-----------------------------	---------------

G-ESIS-M12-S68N-PEPDS-BK - Cable gland



1424465

<https://www.phoenixcontact.com/us/products/1424465>

Halogen-free	yes
--------------	-----

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP66
	IP68 (5 bar / 0.5 h)
Ambient temperature (operation)	-40 °C ... 75 °C (static)

G-ESIS-M12-S68N-PEPDS-BK - Cable gland



1424465

<https://www.phoenixcontact.com/us/products/1424465>

Classifications

ECLASS

ECLASS-11.0	27144432
ECLASS-12.0	27140801
ECLASS-13.0	27140802

ETIM

ETIM 9.0	EC000441
----------	----------

UNSPSC

UNSPSC 21.0	39121300
-------------	----------

G-ESIS-M12-S68N-PEPDS-BK - Cable gland



1424465

<https://www.phoenixcontact.com/us/products/1424465>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e No hazardous substances above threshold values
------------	---

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com