

# G-ESIS-M32-S68N-PEPDS-BK - Cable gland



1424469

<https://www.phoenixcontact.com/us/products/1424469>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable gland, material for screw connection: PA, application: Ex, external cable diameter 13 mm .  
.. 21 mm, shielding: no, connecting thread: M32 x 1.5, color: jet black RAL 9005, with flat gasket

## Product description

Cable gland, with flat gasket

## Your advantages

- Glow-wire test: 750°C
- Weatherproof sealing material
- Halogen-free

## Commercial data

Item number	1424469
Packing unit	5 pc
Minimum order quantity	10 pc
Product key	BF7DDX
GTIN	4055626375595
Weight per piece (including packing)	40.46 g
Weight per piece (excluding packing)	22.22 g
Country of origin	DE

# G-ESIS-M32-S68N-PEPDS-BK - Cable gland



1424469

<https://www.phoenixcontact.com/us/products/1424469>

## Technical data


### Product properties

Product type	Full screw connection
Application	Ex
No. of conductors	1
Manufacturer	WISKA
Manufacturer Designation	ESKE/1-e 32
Shielded	no

### Ex data

Cable types that can be used	for unarmored cables
Suited for EX-applications	yes

### Dimensions

Dimensional drawing	
Length	48 mm
Length of the connecting thread	12 mm
Hole diameter	32.1 mm ... 32.3 mm
Wrench size, union nut	36 mm
Wrench size, support	36 mm
Hexagon angular dimension	41 mm
Thread type connection side	M32 x 1.5
Thread pitch	1.5 mm

### Connection data

Tightening torque	4.5 Nm (Support sleeve)
-------------------	-------------------------

### Material specifications

Color	black (RAL 9005)
Material Screw connection	PA
Seal material Flat gasket	EPDM
Glow wire ignition temperature GWIT according to EN 60695-2-13	750
Material for screw connection	PA

### Cable/line

External cable diameter ( )	13 mm ... 21 mm
-----------------------------	-----------------

# G-ESIS-M32-S68N-PEPDS-BK - Cable gland



1424469

<https://www.phoenixcontact.com/us/products/1424469>

Halogen-free	yes
--------------	-----

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP66
	IP68 (5 bar / 0.5 h)
Ambient temperature (operation)	-40 °C ... 75 °C (static)

# G-ESIS-M32-S68N-PEPDS-BK - Cable gland



1424469

<https://www.phoenixcontact.com/us/products/1424469>

## Classifications

### ECLASS

ECLASS-11.0	27144432
ECLASS-12.0	27140801
ECLASS-13.0	27140802

### ETIM

ETIM 9.0	EC000441
----------	----------

### UNSPSC

UNSPSC 21.0	39121300
-------------	----------

# G-ESIS-M32-S68N-PEPDS-BK - Cable gland



1424469

<https://www.phoenixcontact.com/us/products/1424469>

## Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)