

# G-INS-PG9-M68N-PNES-LG - Cable gland



1424486

<https://www.phoenixcontact.com/us/products/1424486>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable gland, material for screw connection: PA, external cable diameter 4 mm ... 8 mm, shielding: no, connecting thread: Pg9, color: lightgrey RAL 7035

## Your advantages

- Plastic material conforms to UL 746C f1

## Commercial data

Item number	1424486
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	BF68
Product key	BF7DCX
Catalog page	Page 687 (C-2-2019)
GTIN	4055626373164
Weight per piece (including packing)	6.21 g
Weight per piece (excluding packing)	6.21 g
Customs tariff number	39269097
Country of origin	TR

# G-INS-PG9-M68N-PNES-LG - Cable gland



1424486

<https://www.phoenixcontact.com/us/products/1424486>

## Technical data


### Mounting

Assembly instructions	1) Mount screw connection support in the housing using the correct torque 2) Insert cable 3) Tighten union nut using the correct torque
-----------------------	---

### Product properties

Product type	Full screw connection
No. of conductors	1
Manufacturer	BIMED
Manufacturer Designation	BS-12
Shielded	no

### Dimensions

Dimensional drawing	
Length	36 mm
Length of the connecting thread	8 mm
Hole diameter	15.3 mm ... 15.4 mm
Wrench size, union nut	19 mm
Wrench size, support	19 mm
Hexagon angular dimension	21.6 mm
Thread type connection side	Pg9

### Connection data

Tightening torque	2.5 Nm $\pm$ 0.5 Nm (Cap nut)
	1.5 Nm (Support sleeve)

### Material specifications

Color	light grey (RAL 7035)
Flammability rating according to UL 94	V2
Seal material Cable seal	CR
Material for screw connection	PA

### Cable/line

External cable diameter ( )	4 mm ... 8 mm
	4 mm ... 8 mm (for UL 514 B)

### Environmental and real-life conditions

# G-INS-PG9-M68N-PNES-LG - Cable gland



1424486

<https://www.phoenixcontact.com/us/products/1424486>

## Ambient conditions

Degree of protection	IP66
	IP68 (5 bar / 0.5 h)
Enclosure rating (NEMA)	1
	4
	4X
	12
Ambient temperature (operation)	13
	-40 °C ... 100 °C (static)

# G-INS-PG9-M68N-PNES-LG - Cable gland



1424486

<https://www.phoenixcontact.com/us/products/1424486>

## Classifications

### ECLASS

ECLASS-11.0	27144432
ECLASS-12.0	27140801
ECLASS-13.0	27140801

### ETIM

ETIM 9.0	EC000441
----------	----------

### UNSPSC

UNSPSC 21.0	39121300
-------------	----------

# G-INS-PG9-M68N-PNES-LG - Cable gland



1424486

<https://www.phoenixcontact.com/us/products/1424486>

## Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)