


FO patch cable - FOC-ST:A-ST:A-GB07/10,0 - 1420807

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Assembled FO cable, break out cable, single mode fiberglass 9/125 µm, connector: B-FOC (ST) / B-FOC (ST), protection type: IP20, for installation in cable ducts or control cabinets, length: 10 m





Key Commercial Data

Packing unit	1
GTIN	4 055626 242934
GTIN	4055626242934
Custom tariff number	85444290

Technical data

Mechanical characteristics

Insertion/withdrawal cycles	≥ 500
Weight	182.7 g

Ambient conditions

Ambient temperature (operation)	-5 °C 70 °C
Ambient temperature (assembly)	-5 °C 50 °C
Ambient temperature (storage/transport)	-25 °C 70 °C

Line characteristics

Cable type	Single-mode fiberglass
External cable diameter	2.8 mm
Transmission medium	FO
Fiber	Single mode
Cable, attenuation	0.3 dB/km (at 1310 nm), 0.2 dB/km (at 1550 nm)



FO patch cable - FOC-ST:A-ST:A-GB07/10,0 - 1420807

Technical data

Line characteristics

Attenuation	≤ 0.5 dB

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50 years
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss

eCl@ss 10.0.1	27061003
eCl@ss 11.0	27061003
eCl@ss 9.0	27061003

ETIM

ETIM 6.0	EC001263
ETIM 7.0	EC001263

UNSPSC

UNSPSC 13.2	26121607
UNSPSC 18.0	26121607
UNSPSC 19.0	26121607
UNSPSC 20.0	26121607
UNSPSC 21.0	26121607

Phoenix Contact 2021 © - all rights reserved http://www.phoenixcontact.com