

G-INVEN-M16-M67N-PNES-BK - Cable gland



1424536

<https://www.phoenixcontact.com/us/products/1424536>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable gland, material for screw connection: PA, external cable diameter 4 mm ... 7 mm, shielding: no, connecting thread: M16 x 1.5, color: jet black RAL 9005, with pressure compensation element and flat gasket

Product description

Cable gland with integrated pressure compensation element. Prevents low pressure forming in the housing. Membrane: resistant to water and dirt

Your advantages

- Reduces the formation of condensation
- Screw connection with integrated pressure compensation element
- Plastic material conforms to UL 746C f1

Commercial data

Item number	1424536
Packing unit	5 pc
Minimum order quantity	5 pc
Sales key	BF68
Product key	BF7DCX
Catalog page	Page 694 (C-2-2019)
GTIN	4055626374413
Weight per piece (including packing)	7.16 g
Weight per piece (excluding packing)	6.97 g
Customs tariff number	39269097
Country of origin	TR

G-INVEN-M16-M67N-PNES-BK - Cable gland



1424536

<https://www.phoenixcontact.com/us/products/1424536>

Technical data


Product properties

Product type	Full screw connection
No. of conductors	1
Type	with pressure compensation element and flat gasket
Manufacturer	BIMED
Manufacturer Designation	BMVG-21
Air flow rate	25 (l/h at a pressure differential of 70 mbar)
Shielded	no
Execution of the strain relief	A

Characteristics

Category of shock impact	5
Design, Strain relief	A

Dimensions

Dimensional drawing	
Length	35.5 mm
Length of the connecting thread	10 mm
Hole diameter	16.1 mm ... 16.2 mm
Wrench size, union nut	19 mm
Wrench size, support	19 mm
Thread type connection side	M16 x 1.5
Thread pitch	1.5 mm

Connection data

Tightening torque	2 Nm \pm 0.2 Nm (Cap nut)
	2.5 Nm (Support sleeve)

Material specifications

Color	black (RAL 9005)
Material	PTFE
Flammability rating according to UL 94	V2
Seal material Flat gasket	NBR
Seal material Cable seal	CR
Material for screw connection	PA

Cable/line

External cable diameter (Cable 1)	4 mm ... 7 mm
-----------------------------------	---------------

G-INVEN-M16-M67N-PNES-BK - Cable gland



1424536

<https://www.phoenixcontact.com/us/products/1424536>

External cable diameter ()	4 mm ... 8 mm (for UL 514 B)
Halogen-free	no

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP67
	IP66
Enclosure rating (NEMA)	1
	4
	4X
	12
	13
Ambient temperature (operation)	-20 °C ... 100 °C (static)

G-INVEN-M16-M67N-PNES-BK - Cable gland



1424536

<https://www.phoenixcontact.com/us/products/1424536>

Classifications

ECLASS

ECLASS-11.0	27144432
ECLASS-12.0	27140801
ECLASS-13.0	27140801

ETIM

ETIM 9.0	EC000441
----------	----------

UNSPSC

UNSPSC 21.0	39121300
-------------	----------

G-INVEN-M16-M67N-PNES-BK - Cable gland



1424536

<https://www.phoenixcontact.com/us/products/1424536>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e No hazardous substances above threshold values
------------	---

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com