TBUS8-20,0-PPPPPPP-7035 - DIN rail bus connectors



2202889

https://www.phoenixcontact.com/us/products/2202889

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



DIN rail connector, color: light grey, nominal current: 6 A (parallel contacts), rated voltage (III/2): 32 V, number of positions: 8, pitch: 2.54 mm, mounting: DIN rail mounting, locking: without, mounting: without, type of packaging: packed in cardboard, Item with gold-plated contacts, bus connectors for connecting with electronics housings, 8 parallel contacts

Your advantages

- · Space-saving installation under the housing in the DIN rail
- · Contact design enables electronics modules to be easily snapped on
- · Power supply and communication without additional wiring
- · Parallel and serial contacts for efficient signal and data transmission

Commercial data

Item number	2202889
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	AC09
Product key	ACHAGA
GTIN	4055626382135
Weight per piece (including packing)	5.9 g
Weight per piece (excluding packing)	4.53 g
Customs tariff number	85366990
Country of origin	PL

TBUS8-20,0-PPPPPPP-7035 - DIN rail bus connectors



2202889

https://www.phoenixcontact.com/us/products/2202889

Technical data

Notes

Recommendation	Material of contact pads for bus connector, galvanic gold (hard gold)	
Product properties		
Product type	DIN rail connector	
Product family	TBUS8-2PP	
Number of positions	8	
Pitch	2.54 mm	

Electrical properties

Nominal current I _N	6 A (parallel contacts)
Nominal voltage U _N	32 V
Degree of pollution	3
Rated voltage (III/2)	32 V
Rated surge voltage (III/2)	1.5 kV
Rated voltage (II/2)	32 V
Rated surge voltage (II/2)	1.5 kV

Connection data

Dimensions

Pitch	2.54 mm
Width [w]	24.3 mm
Height [h]	37.15 mm
Length [I]	16.3 mm

Material specifications

Material data - contact		
Contact material	Cu alloy	
Surface characteristics	gold-plated	
Material data - housing		
Color (Housing)	light grey (7035)	
Insulating material	PA	
Insulating material group	1	
CTI according to IEC 60112	600	
Flammability rating according to UL 94	VO	

Connector

Connection 1



2202889

https://www.phoenixcontact.com/us/products/2202889

Insulating material	PA
CTI according to IEC 60112	600

Electrical tests

Air clearances and creepage distances |

Specification	IEC 60664-1:2007-04
Insulating material group	1
Rated insulation voltage (III/2)	32 V
Rated surge voltage (III/2)	1.5 kV
minimum clearance value - non-homogenous field (III/2)	0.5 mm
minimum creepage distance (III/2)	0.53 mm
Rated insulation voltage (II/2)	32 V
Rated surge voltage (II/2)	1.5 kV
minimum clearance value - non-homogenous field (II/2)	0.5 mm
minimum creepage distance (II/2)	0.53 mm

Environmental and real-life conditions

Ambient conditions	
Ambient temperature (operation)	-40 °C 105 °C (dependent on the derating curve)
Ambient temperature (storage/transport)	-40 °C 55 °C
Relative humidity (storage/transport)	30 % 70 %
Ambient temperature (assembly)	-5 °C 100 °C

Mounting

	Mounting type	DIN rail mounting
Packaging specifications		
	Type of packaging	packed in cardboard
	Outer packaging type	Carton



2202889

https://www.phoenixcontact.com/us/products/2202889

Classifications

ECLASS

ECLASS-11.0	27460201
ECLASS-12.0	27460201
ECLASS-13.0	27460201

ETIM

	ETIM 9.0	EC002637	
UN	UNSPSC		
	UNSPSC 21.0	39121400	

TBUS8-20,0-PPPPPPP-7035 - DIN rail bus connectors



2202889

https://www.phoenixcontact.com/us/products/2202889

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com