

FLX-D37F/32CH/DO/TDC3K - Interface module



2908892

<https://www.phoenixcontact.com/us/products/2908892>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Migration board for converting TDC3000 to modern control platforms, digital output, 32 channel

Your advantages

- Panel mount to existing TDC3000 chassis
- Compatible with existing pluggable field wiring connectors
- DSUB control side connection
- Terminal blocks for power supply

Commercial data

Item number	2908892
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	C421
Product key	CK21A3
GTIN	4055626733098
Weight per piece (including packing)	525 g
Weight per piece (excluding packing)	500 g
Customs tariff number	85176200
Country of origin	US

FLX-D37F/32CH/DO/TDC3K - Interface module



2908892

<https://www.phoenixcontact.com/us/products/2908892>

Technical data

Product properties

Product type	Interface module
--------------	------------------

Insulation characteristics

Overvoltage category	II
Pollution degree	2

Electrical properties

Max. operating voltage U_{max}	30 V DC (Power supply)
Operating voltage	30 V DC
Max. current carrying capacity per branch	500 mA
Maximum power voltage feed	5 A (fuse limited)

Supported controller HONEYWELL TDC3000

Suitable I/O card	TDOY22
-------------------	--------

Connection data

Controller level

Connection method	D-SUB 37 female connector
Number of connections	2
Number of positions	37

Field level

Connection method	pluggable
-------------------	-----------

Dimensions

Item dimensions

Width	307.3 mm
Height	120.7 mm
Depth	38.3 mm

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 75 °C
Altitude	< 2000 m
Permissible humidity (operation)	< 90 %

Mounting

Mounting position	any
-------------------	-----

Notes

FLX-D37F/32CH/DO/TDC3K - Interface module



2908892

<https://www.phoenixcontact.com/us/products/2908892>

General

For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.

FLX-D37F/32CH/DO/TDC3K - Interface module



2908892

<https://www.phoenixcontact.com/us/products/2908892>

Classifications

ECLASS

ECLASS-11.0	27141152
ECLASS-12.0	27141152
ECLASS-13.0	27141152

ETIM

ETIM 9.0	EC002780
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

FLX-D37F/32CH/DO/TDC3K - Interface module



2908892

<https://www.phoenixcontact.com/us/products/2908892>

Environmental product compliance

REACH SVHC

Lead 7439-92-1

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com