


String combiner box (SCB) - SOL-SC1-16ST-0-F1-21 - 1053571

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



String combiner box for photovoltaic systems up to 1,000 V DC for the connection of up to 16 strings. With one-sided fuse protection via fuse holder. Cable entry via multiple cable gland. Including 15 A fuse-links.

Product Description

The Solarline string combiner boxes (SCBs) are used in both small rooftop systems and large ground-mounted systems. Their functions include collecting and protecting strings and, if necessary, separating the panels from the rest of the system by means of a switch disconnecter or fire service switch disconnecter.

Your advantages

- ✓ Large portfolio of string combiner boxes in stock
- ✓ Application-oriented analysis and consultation
- ✓ Use of the best connection technologies and suitable components
- ✓ Durable and error-free operation, thanks to comprehensively tested solutions
- ✓ Standard-compliant switchgear and controlgear assembly, thanks to use of DIN EN 61439



Key Commercial Data

Packing unit	1
GTIN	
GTIN	4055626685656
Custom tariff number	85363090

Technical data

System parameter

System voltage	1000 V DC (U_{max})
Number of string inputs	16
Current per string (typical)	9 A (I_{nc})

String combiner box (SCB) - SOL-SC1-16ST-0-F1-21 - 1053571

Technical data

System parameter

Current per string (max.)	12.5 A (I_{max} , with limited temperature range)
Number of outputs	1 (per MPP tracker)
Number of supported MPP trackers	(not relevant)

Safety equipment

String fuse	10:3 x 38 mm (in scope of delivery)
-------------	-------------------------------------

Cable entry

Type of cable entry	Cable gland
Cable cross section string input	4 mm ² ... 6 mm ²
Sealing area string input	5 mm ... 7 mm
Cable cross section output	120 mm ²
Sealing area output	16 mm ... 28 mm
Bolt diameter output (cable lug)	10 mm

General data

Housing material	Fiberglass-reinforced plastic
Weight	8300 g
Installation location	Outdoor installation, roofed area, no direct sunlight
Degree of protection	IP65
Protection class	II
Impact strength	IK10

Dimensions

Outer dimensions: width, height, depth	400 mm x 400 mm x 200 mm (Housing dimensions)
--	---

Ambient conditions

Ambient temperature (operation)	-20 °C ... 45 °C
---------------------------------	------------------

Standards and Regulations

Standards/specifications	IEC 61439-2
--------------------------	-------------

Classifications

eCl@ss

eCl@ss 10.0.1	27142422
eCl@ss 11.0	27142422
eCl@ss 5.1	27371890
eCl@ss 7.0	27142422
eCl@ss 9.0	27142422

String combiner box (SCB) - SOL-SC1-16ST-0-F1-21 - 1053571

Classifications

ETIM

ETIM 4.0	EC000816
ETIM 6.0	EC000268
ETIM 7.0	EC000268