

BLUEMARK ID - Printer

1003334

<https://www.phoenixcontact.com/us/products/1003334>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Monochrome printer with UV LED technology and integrated “MARKING system app” identification software. 7” touch color display for printing plastic tags in UC, UCT, US, and UM format, as well as metal labels.

Your advantages

- Intuitive and time-saving operation using integrated marking software and a graphical user interface
- Marking that is instantly wipe-resistant, so that marking materials are ready for immediate use
- Rapid marking of plastic and metal labels for marking terminals, conductors, cables, devices, and plants
- Scalable print resolution between standard (300 dpi) and HD printing (600 dpi)
- Environmentally-sound, emission-free high-speed printer with modern UV LED technology
- The printer detects the direction of the inserted sheets and automatically rotates printing 180° if required

Commercial data

Item number	1003334
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BG01
Product key	BG1211
Catalog page	Page 33 (C-3-2019)
GTIN	4055626471075
Weight per piece (including packing)	32 kg
Weight per piece (excluding packing)	27.5 kg
Customs tariff number	84433210
Country of origin	DE

Technical data

Product properties

Product type	Printing system
Marking	
Identification technology	UV LED technology
Device properties	
Operating system	MS Windows 7 (32/64-bit), MS Windows 8 (32/64-bit), MS Windows 8.1 (32/64-bit), MS Windows 10 (32/64-bit), MS Windows 11 (32/64-bit)

Electrical properties

Supply	
Supply voltage range	100 V AC ... 240 V AC (50 Hz ... 60 Hz)

Interfaces

Interface	10/100 Mbps Ethernet, 1x USB 2.0 device, 1x USB 2.0 Host
-----------	--

Dimensions

Width	523 mm
Height	340 mm
Length	675 mm

Material specifications

Material Plastic signs	UC
	UCT
	US
	UM

Environmental and real-life conditions

Ambient conditions	
Ambient temperature (operation)	5 °C ... 35 °C

1003334

<https://www.phoenixcontact.com/us/products/1003334>

Classifications

ECLASS

ECLASS-11.0	19140103
ECLASS-12.0	19140103
ECLASS-13.0	19140103

ETIM

ETIM 9.0	EC001684
----------	----------

UNSPSC

UNSPSC 21.0	43212100
-------------	----------

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com