



## End cover - D-BT 1,25-F - 1012516

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



End cover, with flange on the right-hand side, length: 42 mm, width: 17.4 mm, height: 26 mm, color: black

### Key Commercial Data

Packing unit	1
GTIN	 4 055626 490137
GTIN	4055626490137
Custom tariff number	85389099

### Technical data

#### General

Color	black
Material	PC
Flammability rating according to UL 94	V0
Overvoltage category	III
Insulating material group	IIIa

#### Dimensions

Width	17.4 mm
End cover width	3.5 mm
Length	42 mm
Height	26 mm

#### Ambient conditions

Operating temperature	-60 °C ... 85 °C
-----------------------	------------------

# End cover - D-BT 1,25-F - 1012516

## Technical data

### Ambient conditions

Ambient temperature (storage/transport)	-25 °C ... 55 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Permissible humidity (storage/transport)	30 % ... 70 %
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C

### Standards and Regulations

Flammability rating according to UL 94	V0
--	----

### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

## Classifications

### eCl@ss

eCl@ss 10.0.1	27141133
eCl@ss 11.0	27141133
eCl@ss 4.0	21011300
eCl@ss 4.1	21011300
eCl@ss 5.0	27141100
eCl@ss 5.1	27141145
eCl@ss 6.0	27141100
eCl@ss 7.0	27141133
eCl@ss 9.0	27141133

### ETIM

ETIM 4.0	EC000886
ETIM 6.0	EC000886
ETIM 7.0	EC000886

### UNSPSC

UNSPSC 6.01	30211827
UNSPSC 7.0901	39121424
UNSPSC 11	39121424
UNSPSC 12.01	39121424
UNSPSC 13.2	39121425
UNSPSC 18.0	39121425
UNSPSC 19.0	39121425
UNSPSC 20.0	39121425

## End cover - D-BT 1,25-F - 1012516

### Classifications

#### UNSPSC

UNSPSC 21.0	39121425
-------------	----------