

# BWP 2043W - Web panel



1060549

<https://www.phoenixcontact.com/us/products/1060549>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Web panel with 10.92 cm / 4.3" TFT display (analog resistive), 480 x 272 pixel(s) (WQVGA), 16.7 million colors, i.MX 6DualLite, 1 GHz, 1x USB Host 2.0, 1 x Ethernet (10/100 Mbps), RJ45, Yocto/Linux<sup>®</sup> and user software: QT browser. (bus system: without)

## Commercial data

Item number	1060549
Packing unit	1 pc
Sales key	DR17
Product key	DRCEBF
Catalog page	Page 468 (C-6-2019)
GTIN	4055626711386
Weight per piece (including packing)	320 g
Weight per piece (excluding packing)	324 g
Customs tariff number	84714100
Country of origin	IN

# BWP 2043W - Web panel



1060549

<https://www.phoenixcontact.com/us/products/1060549>

## Technical data

### Product properties

Product type	Operator panel
--------------	----------------

### Computer data

Processor	i.MX 6DualLite, 1 GHz
Operating system	Yocto/Linux®
RAM	1 GB DDR3 SDRAM
Data storage system	Flash eMMC, 4 GB

### Display

Display type	10.92 cm / 4.3" TFT
Screen resolution	480 x 272 Pixel(s) (WQVGA)
Touch technology	analog resistive
Display lighting type	LED
Brightness	350 cd/m <sup>2</sup>
MTBF	20000 h
Color spectrum	16.7 million colors
Reading angle left	70.00 °
Reading angle right	70.00 °
Reading angle top	50.00 °
Reading angle bottom	70.00 °

### Software

User software	QT browser
---------------	------------

### Interfaces

Interfaces	1x USB Host 2.0
Network	1 x Ethernet (10/100 Mbps), RJ45
Bus system	without

### System properties

User software	QT browser
---------------	------------

### Electrical properties

#### Supply

Power supply unit	24 V DC ±15 %
Typical current consumption	0.22 A

### Mounting

Mounting type	Front mounting
---------------	----------------

### Material specifications

# BWP 2043W - Web panel



1060549

<https://www.phoenixcontact.com/us/products/1060549>

Material front plate	Plastic
Housing material	Plastic

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP66 (front), IP20 (back)
Ambient temperature (operation)	0 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 85 °C
Permissible humidity (operation)	10 % ... 95 % (non-condensing)
Permissible humidity (storage/transport)	10 % ... 95 % (non-condensing)
Shock	DIN EN 60068-2-27
Vibration (operation)	DIN EN 60068-2-6

## Dimensions

### External dimensions

Width / Height / Depth	120 mm / 89 mm / 5 mm (Dimensions of the front plate)
------------------------	---

### Installation dimensions

Width / Height / Installation depth	111 mm / 80 mm / 31.5 mm (Installation cutout)
-------------------------------------	--

1060549

<https://www.phoenixcontact.com/us/products/1060549>

## Classifications

### ECLASS

ECLASS-11.0	27330201
ECLASS-12.0	27330201
ECLASS-13.0	27330201

### ETIM

ETIM 9.0	EC001412
----------	----------

### UNSPSC

UNSPSC 21.0	43211900
-------------	----------

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)