

# SAC-3P-M12MSS/ 5,0-PVC PE - Power cable



1411638

<https://www.phoenixcontact.com/us/products/1411638>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Power cable, 3-position, PVC, black, Plug straight M12, coding: S, on free cable end, cable length: 5 m, For alternating current up to 16 A/690 V

## Your advantages

- Easy and safe: 100 % electrically tested plug-in components
- Protection against incorrect connection using special S-coding

## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 1411638             |
| Packing unit                         | 1 pc                |
| Minimum order quantity               | 1 pc                |
| Sales key                            | BF05                |
| Product key                          | BF1CBB              |
| Catalog page                         | Page 288 (C-2-2019) |
| GTIN                                 | 4046356937382       |
| Weight per piece (including packing) | 435.8 g             |
| Weight per piece (excluding packing) | 440.3 g             |
| Customs tariff number                | 85444290            |
| Country of origin                    | DE                  |

# SAC-3P-M12MSS/ 5,0-PVC PE - Power cable



1411638

<https://www.phoenixcontact.com/us/products/1411638>

## Technical data

### Product properties

|                      |              |
|----------------------|--------------|
| Product type         | Power cable  |
| Number of positions  | 3            |
| Application          | Power supply |
| No. of cable outlets | 1            |
| Shielded             | no           |
| Coding               | S            |

### Insulation characteristics

|                      |     |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution  | 3   |

### Material specifications

|  |                              |
|--|------------------------------|
| Flammability rating according to UL 94 | V0                           |
| Material of grip body                  | PP                           |
| Contact material                       | CuZn                         |
| Contact surface material               | Ni/Au                        |
| Contact carrier material               | PA                           |
| Material for screw connection          | Zinc die-cast, nickel-plated |

### Electrical properties

|                       |                            |
|-----------------------|----------------------------|
| Insulation resistance | $\geq 100 \text{ M}\Omega$ |
| Nominal voltage $U_N$ | 690 V AC                   |
| Nominal current $I_N$ | 16 A                       |
| Protective circuit    | unwired                    |

### Mechanical properties

#### Mechanical data

|                             |       |
|-----------------------------|-------|
| Insertion/withdrawal cycles | > 100 |
|-----------------------------|-------|

### Connector

#### Connection 1

|             |                   |
|-------------|-------------------|
| Type        | Plug straight M12 |
| Coding type | S (Power)         |

#### Connection 2

|      |                |
|------|----------------|
| Type | free cable end |
|------|----------------|

### Cable/line

|              |     |
|--------------|-----|
| Cable length | 5 m |
|--------------|-----|


PVC black [PVC]

# SAC-3P-M12MSS/ 5,0-PVC PE - Power cable



1411638

<https://www.phoenixcontact.com/us/products/1411638>

|   |  |
|---|--|
| Dimensional drawing                           |                  |
| Cable weight                                  | 80 kg/km   |
| UL AWM Style                                  | 2517 (105 °C / 300 V)  |
| Number of positions                           | 3  |
| Shielded                                      | no   |
| Cable type                                    | PVC black [PVC]  |
| Conductor cross section                       | 3x 1.5 mm <sup>2</sup>   |
| Wire diameter incl. insulation                | 2.4 mm ±0.1 mm   |
| External cable diameter                       | 6.80 mm ±0.2 mm  |
| Outer sheath, material                        | PVC  |
| External sheath, color                        | black  |
| Conductor material                            | Bare Cu litz wires   |
| Material wire insulation                      | PVC  |
| Single wire, color                            | black 1, black 2, green/yellow   |
| Overall twist                                 | 3 wires, twisted   |
| Max. conductor resistance                     | ≤ 13.3 Ω/km (at 20 °C)   |
| Insulation resistance                         | ≥ 10 MΩ*km (at 20 °C)  |
| Nominal voltage, cable                        | 300 V AC   |
| Test voltage                                  | 2000 V AC  |
| Minimum bending radius, fixed installation    | 5 x D  |
| Minimum bending radius, flexible installation | 12 x D   |
| Smallest bending radius, fixed installation   | 34 mm  |
| Smallest bending radius, movable installation | 82 mm  |
| Flame resistance                              | according to IEC 60332-1<br>According to DIN EN 60332-1-2<br>According to VW-1<br>According to FT1 |
| Ambient temperature (operation)               | -40 °C ... 90 °C (cable, fixed installation)<br>-5 °C ... 90 °C (Cable, flexible installation)     |

## Environmental and real-life conditions

### Ambient conditions

|                                 |  |
|---------------------------------|--|
| Degree of protection            | IP65<br>IP67 (without preloading, as additional test in accordance with IEC 60529) |
| Ambient temperature (operation) | -25 °C ... 85 °C (Plug / socket)   |

# SAC-3P-M12MSS/ 5,0-PVC PE - Power cable



1411638

<https://www.phoenixcontact.com/us/products/1411638>

## Standards and regulations

|                          |                 |
|--------------------------|-----------------|
| Standard designation     | M12 connector   |
| Standards/specifications | IEC 61076-2-111 |

# SAC-3P-M12MSS/ 5,0-PVC PE - Power cable



1411638

<https://www.phoenixcontact.com/us/products/1411638>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27060311 |
| ECLASS-12.0 | 27060311 |
| ECLASS-13.0 | 27060327 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC001855 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 26121600 |
|-------------|----------|

# SAC-3P-M12MSS/ 5,0-PVC PE - Power cable



1411638

<https://www.phoenixcontact.com/us/products/1411638>

## Environmental product compliance

|            |   |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)