

QPD N2,5 9-14 BK - Nut

1423994

<https://www.phoenixcontact.com/us/products/1423994>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Nut, product family: QPD, connection method: IDC connection, 1 mm² ... 2.5 mm², 690 V, 20 A, PA, black, external cable diameter: 9 mm ... 14 mm

Your advantages

- Innovative and time saving - QUICKON fast connection for time saving of up to 80 % for on-site connection
- Robust throughout: housing with IP68/IP69K and IK07 protection for a wide range of applications

Commercial data

| | |
|--------------------------------------|---------------------|
| Item number | 1423994 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | BF50 |
| Product key | BF6UCX |
| Catalog page | Page 481 (C-2-2019) |
| GTIN | 4055626366111 |
| Weight per piece (including packing) | 21.3 g |
| Weight per piece (excluding packing) | 20.5 g |
| Customs tariff number | 85389099 |
| Country of origin | PL |

QPD N2,5 9-14 BK - Nut

1423994

<https://www.phoenixcontact.com/us/products/1423994>



Technical data

Product properties

| | |
|-----------------------|---------------------------|
| Type | QPD 4x2,5 |
| Product type | Installation pressure nut |
| Product family | QPD |
| Number of positions | 4 |
| Position marking | 1, 2, 3, 4 |
| Number of connections | 10 |

Insulation characteristics

| | |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution | 3 |

Electrical properties

| | |
|-----------------------------|--------|
| Rated surge voltage (II/2) | 6 kV |
| Rated surge voltage (III/2) | 6 kV |
| Rated surge voltage (III/3) | 6 kV |
| Rated current | 20 A |
| rated voltage (II/2) | 1000 V |
| rated voltage (III/2) | 690 V |
| Rated voltage (III/3) | 690 V |
| Nominal current I_N | 20 A |

Connection data


Connection technology

| | |
|---|----------------|
| Connection method On the field side | IDC connection |
| Frequency of connections between conductors of the same cross section | max. 10 |

Conductor connection

| | |
|----------------------------------|---|
| Conductor cross section flexibel | 1 mm ² ... 2.5 mm ² |
| Conductor cross section solid | 1 mm ² ... 2.5 mm ² |
| Connection cross section AWG | 16 ... 14 |
| Tightening torque Union nut | 7 Nm |

Dimensions

| | |
|---------------------|--|
| Dimensional drawing |  |
| Width | 30 mm |
| Height | 30 mm |
| Length | 40 mm |

QPD N2,5 9-14 BK - Nut



1423994

<https://www.phoenixcontact.com/us/products/1423994>

| | |
|----------|-------|
| Diameter | 30 mm |
|----------|-------|

Material specifications

| | |
|--|-------------------------|
| Color | black (RAL 9005) |
| Material Housing | PA |
| Flammability rating according to UL 94 | V0 |
| Material wire insulation | PVC / PE / rubber / TPE |
| Contact carrier material | PA |

Cable/line

| | |
|---|------------------------------------|
| Structure of individual litz in acc. with VDE 0295 / smallest wire diameter | VDE 0295 class 1 to 6/min. 0.15 mm |
| External cable diameter () | 9 mm ... 14 mm |
| Wire diameter including insulation | 2 mm ... 3.6 mm |
| Position marking | 1, 2, 3, 4 |
| Material wire insulation | PVC / PE / rubber / TPE |

Environmental and real-life conditions

Ambient conditions

| | |
|---|-------------------|
| Degree of protection | IP66 |
| | IP68 (2 m / 24 h) |
| | IP69K |
| Ambient temperature (operation) | -40 °C ... 100 °C |
| Temperature when conductor connected | -5 °C ... 50 °C |
| Ambient temperature (storage/transport) | -40 °C ... 80 °C |

QPD N2,5 9-14 BK - Nut



1423994

<https://www.phoenixcontact.com/us/products/1423994>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27440691 |
| ECLASS-12.0 | 27440691 |
| ECLASS-13.0 | 27440691 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC002863 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

QPD N2,5 9-14 BK - Nut

1423994

<https://www.phoenixcontact.com/us/products/1423994>



Environmental product compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e No hazardous substances above threshold values |
|------------|---|

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com