

# SAC-4P-10,0-110/M12FRL - Power cable



1425060

<https://www.phoenixcontact.com/us/products/1425060>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Power cable, 4-position, PVC, black-gray RAL 7021, free cable end, on Socket angled M12, coding: L, cable length: 10 m, For direct current up to 12 A/63 V

## Your advantages

- Easy and safe: 100 % electrically tested plug-in components
- Protection against mismatching, thanks to special L-coding

## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 1425060             |
| Packing unit                         | 1 pc                |
| Minimum order quantity               | 1 pc                |
| Sales key                            | BF05                |
| Product key                          | BF1CCR              |
| Catalog page                         | Page 297 (C-2-2019) |
| GTIN                                 | 4055626383989       |
| Weight per piece (including packing) | 1,088.93 g          |
| Weight per piece (excluding packing) | 1,088.93 g          |
| Customs tariff number                | 85444290            |
| Country of origin                    | PL                  |

# SAC-4P-10,0-110/M12FRL - Power cable



1425060

<https://www.phoenixcontact.com/us/products/1425060>

## Technical data

### Product properties

|                      |              |
|----------------------|--------------|
| Product type         | Power cable  |
| Number of positions  | 4            |
| Application          | Power supply |
| No. of cable outlets | 1            |
| Shielded             | no           |
| Coding               | L            |

### Insulation characteristics

|                      |     |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution  | 3   |

### Material specifications

|                                        |                              |
|----------------------------------------|------------------------------|
| Flammability rating according to UL 94 | V0                           |
| Material of grip body                  | PP                           |
| Contact material                       | CuZn                         |
| Contact surface material               | Ni/Au                        |
| Contact carrier material               | PA                           |
| Material for screw connection          | Zinc die-cast, nickel-plated |

### Electrical properties

|                       |                            |
|-----------------------|----------------------------|
| Insulation resistance | $\geq 100 \text{ M}\Omega$ |
| Nominal voltage $U_N$ | 63 V DC                    |
| Nominal current $I_N$ | 12 A                       |
| Protective circuit    | unwired                    |

### Mechanical properties

#### Mechanical data

|                             |            |
|-----------------------------|------------|
| Insertion/withdrawal cycles | $\geq 100$ |
|-----------------------------|------------|

### Connector

#### Connection 1

|      |                |
|------|----------------|
| Type | free cable end |
|------|----------------|

#### Connection 2

|             |                   |
|-------------|-------------------|
| Type        | Socket angled M12 |
| Coding type | L (Power)         |

### Cable/line

|              |      |
|--------------|------|
| Cable length | 10 m |
|--------------|------|


PVC 1.5 mm<sup>2</sup> black [110]

# SAC-4P-10,0-110/M12FRL - Power cable



1425060

<https://www.phoenixcontact.com/us/products/1425060>

|                                               |                                                                                                         |
|-----------------------------------------------|---------------------------------------------------------------------------------------------------------|
| Dimensional drawing                           |                       |
| Cable weight                                  | 108 kg/km                                                                                               |
| UL AWM Style                                  | 20233 / 10493 (80°C/300 V)                                                                              |
| Number of positions                           | 4                                                                                                       |
| Shielded                                      | no                                                                                                      |
| Cable type                                    | PVC 1.5 mm² black [110]                                                                                 |
| Conductor cross section                       | 4x 1.5 mm²                                                                                              |
| Wire diameter incl. insulation                | 2.35 mm ±0.05 mm                                                                                        |
| External cable diameter                       | 7.55 mm ±0.25 mm                                                                                        |
| Outer sheath, material                        | PVC                                                                                                     |
| External sheath, color                        | black-gray RAL 7021                                                                                     |
| Conductor material                            | Bare Cu litz wires                                                                                      |
| Material wire insulation                      | PVC                                                                                                     |
| Single wire, color                            | brown, white, blue, black                                                                               |
| Thickness, insulation                         | ≥ 0.25 mm                                                                                               |
| Thickness, outer sheath                       | approx. 1.30 mm                                                                                         |
| Max. conductor resistance                     | ≤ 13 Ω/km (at 20 °C)                                                                                    |
| Insulation resistance                         | ≥ 1 GΩ*km (at 20 °C)                                                                                    |
| Nominal voltage, cable                        | ≤ 300 V AC                                                                                              |
| Test voltage                                  | ≥ 3000 V AC (Spark test)                                                                                |
| Minimum bending radius, fixed installation    | 5 x D                                                                                                   |
| Minimum bending radius, flexible installation | 10 x D                                                                                                  |
| Smallest bending radius, fixed installation   | 38 mm                                                                                                   |
| Smallest bending radius, movable installation | 76 mm                                                                                                   |
| Max. bending cycles                           | 2000000                                                                                                 |
| Flame resistance                              | According to UL 758/1581 (Cable Flame)<br>according to UL 758/1581 FT1<br>According to DIN EN 60332-1-2 |
| Resistance to oil                             | according to DIN EN 60811-404, 168 h at 60 °C                                                           |
| Ambient temperature (operation)               | -40 °C ... 80 °C (cable, fixed installation)<br>-20 °C ... 80 °C (Cable, flexible installation)         |

## Environmental and real-life conditions

### Ambient conditions

|                      |      |
|----------------------|------|
| Degree of protection | IP65 |
|                      | IP67 |

# SAC-4P-10,0-110/M12FRL - Power cable



1425060

<https://www.phoenixcontact.com/us/products/1425060>

|                                 |                                  |
|---------------------------------|----------------------------------|
| Ambient temperature (operation) | -25 °C ... 85 °C (Plug / socket) |
|---------------------------------|----------------------------------|

### Standards and regulations

|                          |                 |
|--------------------------|-----------------|
| Standard designation     | M12 connector   |
| Standards/specifications | IEC 61076-2-111 |

# SAC-4P-10,0-110/M12FRL - Power cable



1425060

<https://www.phoenixcontact.com/us/products/1425060>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27060311 |
| ECLASS-12.0 | 27060311 |
| ECLASS-13.0 | 27060327 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC001855 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 26121600 |
|-------------|----------|

# SAC-4P-10,0-110/M12FRL - Power cable



1425060  
<https://www.phoenixcontact.com/us/products/1425060>

## Environmental product compliance

|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)