

https://www.phoenixcontact.com/us/products/2909899



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

3-phase loop bridge for 4 CONTACTRON modules, with screw connection and 22.5 mm housing width, cable length between the modules: 0.3 m, connecting cable: 2 m



### Your advantages

- Bridging of 2 to 10 devices with maximum module spacing of 22.5 mm
- · Considerable reduction in wiring
- Up to 575 V AC/3 x 25 A

#### Commercial data

Item number	2909899
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	C470
Product key	CK74Z1
GTIN	4055626408316
Weight per piece (including packing)	308.8 g
Weight per piece (excluding packing)	287.8 g
Customs tariff number	85444290
Country of origin	DE



https://www.phoenixcontact.com/us/products/2909899



## Technical data

### Product properties

Product type	Loop bridge
Product family	CONTACTRON
Number of bridgeable modules	4

### Electrical properties

Operating voltage range	42 V AC 575 V AC
Operating current	≤ 25 A

#### **Dimensions**

Width	22.5 mm	
VVICITI	ZZ.J IIIII	

### Material specifications

|--|

#### Cable/line

Connecting cable length	2 m
Cable cross section	2.5 mm²



https://www.phoenixcontact.com/us/products/2909899



## Classifications

#### **ECLASS**

	ECLASS-11.0	27371392
	ECLASS-12.0	27371392
	ECLASS-13.0	27371392
ET	ТМ	

EC002498

## UNSPSC

ETIM 9.0



https://www.phoenixcontact.com/us/products/2909899



## Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com