

2910417

https://www.phoenixcontact.com/us/products/2910417

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Plug kit for use with VIP/MSTB/D50M/BASE..., push-in connections



### Your advantages

- · Push-in terminal wire connection
- · Pre-printed channel labelling

#### Commercial data

| Item number                          | 2910417                        |
|--------------------------------------|--------------------------------|
| Packing unit                         | 1 pc                           |
| Minimum order quantity               | 1 pc                           |
| Note                                 | Made to order (non-returnable) |
| Sales key                            | NULL                           |
| Product key                          | CK8922                         |
| GTIN                                 | 4055626478791                  |
| Weight per piece (including packing) | 129.2 g                        |
| Weight per piece (excluding packing) | 129 g                          |
| Customs tariff number                | 85366990                       |
| Country of origin                    | DE                             |



2910417

https://www.phoenixcontact.com/us/products/2910417

#### Technical data

#### Product properties

| Product type   | PCB connector       |
|----------------|---------------------|
| Product family | VIP I/O-Marshalling |

#### Electrical properties

| Max. permissible current       | 10 A   |
|--------------------------------|--|
| Nominal voltage U <sub>N</sub> | 300 V (maximum continuous operating voltage) |

#### Connection data

#### Field level

| Connection method                | Push-in spring connection |
|----------------------------------|---------------------------|
| Stripping length                 | 10 mm                     |
| Conductor cross section rigid    | 0.2 mm² 2.5 mm²           |
| Conductor cross section flexible | 0.2 mm² 2.5 mm²           |
| Conductor cross section AWG      | 24 12                     |

#### Material specifications

| Color                                  | gray (RAL 7042) |
|--|-----------------|
| Flammability rating according to UL 94 | V0              |
| Housing insulation material            | PA              |

#### Environmental and real-life conditions

#### Ambient conditions

| Ambient temperature (operation)         | -40 °C 70 °C |
|---|--------------|
| Ambient temperature (storage/transport) | -40 °C 70 °C |



2910417

https://www.phoenixcontact.com/us/products/2910417

## Classifications

UNSPSC 21.0

#### **ECLASS**

| ECLASS-11.0 | 27371392 |
|-------------|----------|
| ECLASS-13.0 | 27371392 |
| ECLASS-12.0 | 27371392 |
| ETIM        |          |
| ETIM 9.0    | EC002498 |
| UNSPSC      |          |

39121100



https://www.phoenixcontact.com/us/products/2910417



### Environmental product compliance

| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|------------|---|
|            | No hazardous substances above threshold values          |

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com