

ID-S-S 868 - Sensor

1061959

<https://www.phoenixcontact.com/us/products/1061959>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Wireless ice and temperature sensor for wind turbine generators, self-adhesive, for mounting on rotor blades, tower or nacelle, communication with the ID-S-RT 868 wireless receiver via 868 MHz frequency band

Product description

The ID-S-S sensor is part of the Blade Intelligence rotor blade monitoring system for wind turbine generators (WTGs). The Blade Intelligence rotor blade monitoring system allows for recording and detailed analysis of typical measured values for lightning currents, temperature, ice thickness, and bending moments on the rotor of a WTG. It consists of the corresponding sensors, preassembled connecting cables, and a WIL-BI switchgear and controlgear assembly (as the evaluation unit).

Your advantages

- Wireless collection and transmission of measurement data
- Ice detection through impedance measurement
- Temperature measurement via integrated switching circuit
- Flexible design
- Simple mounting
- Autonomous operation via integrated solar cell

Commercial data

Item number	1061959
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Product key	DTHABA
GTIN	4055626716367
Weight per piece (including packing)	80 g
Weight per piece (excluding packing)	8,762 g
Country of origin	DE

ID-S-S 868 - Sensor



1061959

<https://www.phoenixcontact.com/us/products/1061959>

Technical data

Product properties

Product type	Sensor
--------------	--------

Interfaces

Wireless

Transmission power	1 mW (minimum)
	10 mW (maximum)

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-40 °C ... 60 °C (Derating at <-25°C)
Ambient temperature (storage/transport)	typ. 0 °C ... 25 °C (Ambient light > 1000 lux)
	max. 0 °C ... 40 °C (Ambient light > 1000 lux)
Permissible humidity (operation)	0 % ... 100 %

EMC data

Electromagnetic HF field

Frequency range	863 MHz ... 870 MHz (typical: 868 MHz)
-----------------	--

ID-S-S 868 - Sensor



1061959

<https://www.phoenixcontact.com/us/products/1061959>

Classifications

ECLASS

ECLASS-11.0	27143137
ECLASS-12.0	27143137
ECLASS-13.0	27143137

ETIM

ETIM 9.0	EC000926
----------	----------

UNSPSC

UNSPSC 21.0	43201500
-------------	----------

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com