

String combiner box (SCB) - SOL-SC-24ST-1-15F1-00000031 - 1118970

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



String combiner box for photovoltaic systems up to 1500 V DC for the connection of up to 24 strings. With one-sided fuse protection via fuse holder. Cable entry via multi-cable gland. Including 15 A fuse-links.

Product Description

The Solarline string combiner boxes (SCBs) are used in both small rooftop systems and large ground-mounted systems. Their functions include collecting and protecting strings and, if necessary, separating the panels from the rest of the system by means of a switch disconnecter or fire service switch disconnecter.

Your advantages

- ✓ Large portfolio of string combiner boxes in stock
- ✓ Application-oriented analysis and consultation
- ✓ Use of the best connection technologies and suitable components
- ✓ Durable and error-free operation, thanks to comprehensively tested solutions
- ✓ Standard-compliant switchgear and controlgear assembly, thanks to use of DIN EN 61439



Key Commercial Data

Packing unit	1
GTIN	
GTIN	4063151048303
Custom tariff number	85372091

Technical data

System parameter

System voltage	1500 V DC (U_{max})
Number of string inputs	24
Current per string (typical)	9 A (I_{nc} , up to 50°C)

String combiner box (SCB) - SOL-SC-24ST-1-15F1-00000031 - 1118970

Technical data

System parameter

	10 A (I_{nc} , up to 45°C)
Current per string (max.)	12.5 A (I_{max} , up to 19°C)
Number of outputs	1
Number of supported MPP trackers	1

Safety equipment

String fuse	10:3 x 38 mm (in scope of delivery)
-------------	-------------------------------------

Cable entry

Type of cable entry	Cable gland
Cable cross section string input	4 mm ² ... 6 mm ²
Sealing area string input	5 mm ... 7 mm
Cable cross section output	300 mm ²
Sealing area output	21 mm ... 35 mm
Bolt diameter output (cable lug)	12 mm

General data

Housing material	Fiberglass-reinforced plastic
Weight	20000 g
Installation location	Outdoor installation, roofed area, no direct sunlight
Degree of protection	IP65
Protection class	II
Impact strength	IK10

Dimensions

Outer dimensions: width, height, depth	535 mm x 735 mm x 270 mm (Housing dimensions)
--	---

Ambient conditions

Ambient temperature (operation)	-20 °C ... 60 °C (Derating starting at 45°C)
---------------------------------	--

Standards and Regulations

Standards/specifications	IEC 61439-2
--------------------------	-------------

Classifications

eCl@ss

eCl@ss 10.0.1	27142422
eCl@ss 11.0	27142422
eCl@ss 5.1	27371890
eCl@ss 7.0	27142422

String combiner box (SCB) - SOL-SC-24ST-1-15F1-00000031 - 1118970

Classifications

eCl@ss

eCl@ss 9.0	27142422
------------	----------

ETIM

ETIM 4.0	EC000268
ETIM 6.0	EC000268
ETIM 7.0	EC000268