

PLC-TR-1T-MUL-300M-PT - Timer relay



2910141

<https://www.phoenixcontact.com/us/products/2910141>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Multi-function timer relay with 4 functions in an ultra-narrow design, adjustable time range (0.1 s - 300 min), 1 changeover contact, Push-in connection

Commercial data

Item number	2910141
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	C442
Product key	CK4521
Catalog page	Page 262 (C-5-2019)
GTIN	4055626430607
Weight per piece (including packing)	38.3 g
Weight per piece (excluding packing)	30 g
Customs tariff number	85364900
Country of origin	DE

PLC-TR-1T-MUL-300M-PT - Timer relay



2910141

<https://www.phoenixcontact.com/us/products/2910141>

Technical data

Product properties

Product type	Timer relay
Operating mode	100% operating factor
Mechanical service life	2×10^7 cycles

Insulation characteristics

Overvoltage category	III
Pollution degree	2

Electrical properties

Service life electrical	2×10^5 cycles
Nominal power consumption	0.45 W (at 24 V DC)
Rated insulation voltage	300 V AC
Rated surge voltage	6 kV

Input data

Nominal power consumption	0.45 W (at 24 V DC)
Input voltage range	24 V DC (19.2 V DC ... 30 V DC)
Recovery time	50 ms
Setting range time	0.1 s ... 300 min. (4 time end ranges)
Setting accuracy	$\leq 2.5 \%$ (of scale end value)
Repeat accuracy	$\leq 0.5 \%$ (of scale end value)

Control

Connection name	Non-floating, terminals A1-B1
Control pulse length	≥ 50 ms

Output data

Switching

Contact switching type	1 floating changeover contact
Maximum switching voltage	250 V AC
Interrupting rating (ohmic load) max.	1500 VA (6 A / 250 V AC)
Output fuse	6.3 A (fast-blow)

Connection data

Connection method	Push-in connection
Stripping length	8 mm
Conductor cross section rigid	0.14 mm ² ... 2.5 mm ²
Conductor cross section flexible	0.14 mm ² ... 2.5 mm ²
Conductor cross section AWG	26 ... 14

Signaling

PLC-TR-1T-MUL-300M-PT - Timer relay



2910141

<https://www.phoenixcontact.com/us/products/2910141>

Status display	Green LED (POWER)
	Yellow LED (relay active)

Dimensions

Width	6.2 mm
Height	80 mm
Depth	86 mm

Material specifications

Color	gray (RAL 7042)
Flammability rating according to UL 94	V0
Housing insulation material	Polyamide PA, self-extinguishing

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-20 °C ... 65 °C
Ambient temperature (storage/transport)	-25 °C ... 80 °C
Altitude	≤ 2000 m
Permissible humidity (operation)	15 % ... 85 %

Approvals

CE

Identification	CE-compliant
----------------	--------------

UL, USA/Canada

Identification	UL/C-UL Listed UL 508
----------------	-----------------------

EMC data

Low Voltage Directive	Conformance with Low Voltage Directive
Noise immunity	EN 61000-6-2
Electromagnetic compatibility	Conformance with EMC directive
Noise emission	EN 61000-6-3

Standards and regulations

Standards/regulations	IEC 61812-1
	IEC 60947-5-1

Mounting

Mounting type	DIN rail mounting
Assembly instructions	on standard DIN rail NS 35 in accordance with EN 60715
Mounting position	any

PLC-TR-1T-MUL-300M-PT - Timer relay



2910141

<https://www.phoenixcontact.com/us/products/2910141>

Classifications

ECLASS

ECLASS-11.0	27371605
ECLASS-12.0	27371605
ECLASS-13.0	27371605

ETIM

ETIM 9.0	EC001439
----------	----------

UNSPSC

UNSPSC 21.0	39122300
-------------	----------

PLC-TR-1T-MUL-300M-PT - Timer relay



2910141

<https://www.phoenixcontact.com/us/products/2910141>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com