

# SCX 2POE 2T - Industrial Ethernet Switch



1108544

<https://www.phoenixcontact.com/us/products/1108544>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Smart Ethernet Box for connecting PoE end devices, two PoE ports, two uplink ports (RJ45), integrated managed switch and surge protection, supply voltage 100 ... 240 V AC, wall or mast mounting

## Product description

The Smart Ethernet Box is used to connect PoE end devices such as IP cameras to a video server. You can use the Smart Ethernet Box to supply voltage to PoE end devices and other external devices. The Smart Ethernet Box is a manageable outdoor PoE switch with a power supply unit, a wiring space for the AC voltage supply, replaceable surge protective modules, and an area with an integrated 24 V DC supply and a DIN rail for mounting additional devices. The Smart Ethernet Box integrates the functions of conventional connection boxes equipped with standard DIN rail devices in a compact device. This saves you time during planning and installation. Numerous management and monitoring functions ensure reliable operation of the system.

## Your advantages

- Cost savings with an all-in-one solution that provides all functions in a single device
- Significant time savings with adapter for wall and mast mounting
- Minimal wiring effort
- Replaceable surge protection
- A wide range of alarm messages via SNMP, such as in the event of sabotage attempts or defective surge protection
- Advanced PoE management for reliable operation of IP cameras
- Quick and easy startup and configuration via web-based management or the FL Network Manager software

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 1108544       |
| Packing unit                         | 1 pc          |
| Minimum order quantity               | 1 pc          |
| Sales key                            | DN08          |
| Product key                          | DNC371        |
| GTIN                                 | 4063151015121 |
| Weight per piece (including packing) | 5,005 g       |
| Weight per piece (excluding packing) | 4,300 g       |
| Customs tariff number                | 85176200      |
| Country of origin                    | DE            |

# SCX 2POE 2T - Industrial Ethernet Switch




1108544

<https://www.phoenixcontact.com/us/products/1108544>

## Technical data

### Dimensions

|                     |  |
|---------------------|--|
| Dimensional drawing |  |
| Width               | 284 mm   |
| Height              | 364 mm   |
| Depth               | 121 mm   |

### Material specifications

|  |   |
|--|---|
| Color (Housing)                        | light grey (RAL 7035)   |
| Material Housing                       | Polycarbonate PC  |
| Material Cable gland                   | Polyamide   |
| Material Cable gland seal, black       | Neoprene  |
| Flammability rating according to UL 94 | V0 (Housing, a vertically clamped sample is extinguished within 10 seconds, no flaming droplets of molten plastic, smoldering for a maximum of 60 seconds)<br>V2 (Cable gland; a vertically tensioned sample is extinguished within 30 seconds; flaming droplets are permitted) |
| Impact strength                        | IK10 (in accordance with IEC 62262: Impact energy of 20 J, corresponds to 5 kg from a height of 40 cm)  |

### Mounting

|               |               |
|---------------|---------------|
| Mounting type | Wall mounting |
|               | Mast mounting |

### Interfaces

|   |  |
|---|--|
| Basic functions                                   | Store-and-forward switch, complies with IEEE 802.3     |
| Data: Ethernet / Fast Ethernet / Gigabit Ethernet |  |
| Transmission speed                                | 10/100/1000 Mbps                                       |
| Connection method                                 | RJ45 jack  |
| No. of channels                                   | 2 (RJ45 ports)   |
| Transmission length                               | 100 m (per segment)                                    |
| Transmission medium                               | Copper   |
| Maximum output power                              | 165 W (>55°C derating, see data sheet)                 |
|   | 155 W (If switching output is active, >55°C derating)  |
|   | 90 W (per port POE1/2, >50°C derating, see data sheet) |

# SCX 2POE 2T - Industrial Ethernet Switch



1108544

<https://www.phoenixcontact.com/us/products/1108544>

## Data: Ethernet / Fast Ethernet / Gigabit Ethernet

|                     |                     |
|---------------------|---------------------|
| Transmission speed  | 10/100/1000 Mbps    |
| Connection method   | RJ45 jack           |
| No. of channels     | 2 (SFP ports)       |
| Transmission length | 100 m (per segment) |
| Transmission medium | Copper              |

## Data: Configuration interface

|                   |               |
|-------------------|---------------|
| Connection method | RJ45 jack     |
| No. of channels   | 1 (RJ45 port) |

## Data: Switching output

|   |   |
|---|---|
| Connection method   | Push-in spring connection   |
| No. of channels   | 1 (Push-in Technology)  |
| Single conductor/terminal point, rigid                                | 0.2 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>                           |
| Single-wire/terminal point, flexible                                  | 0.2 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>                           |
| Conductor cross section, flexible, with ferrule, with plastic sleeve  | 0.25 mm <sup>2</sup> ... 0.75 mm <sup>2</sup> (Stripping length 8 mm) |
| Conductor cross section flexible, with ferrule without plastic sleeve | 0.25 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> (Stripping length 8 mm)  |
| Max. AWG conductor cross section, flexible                            | 16  |
| Min. AWG conductor cross section, flexible                            | 24  |
| Stripping length  | 10 mm   |
| Load/output load current output                                       | no inductive load   |
| Output nominal voltage  | 24 V DC $\pm$ 10 % (Supply for devices within the Smart Ethernet Box) |
| Output current  | 300 mA (typical)  |

## Product properties

|                |   |
|----------------|---|
| Product type   | Switch  |
| Product family | Smart Ethernet Box  |
| MTTF           | 496 Years (SN 29500 standard, temperature 25°C, operating cycle 21%)    |
|                | 247 Years (SN 29500 standard, temperature 40°C, operating cycle 34.25%) |
|                | 105 Years (SN 29500 standard, temperature 40°C, operating cycle 100%)   |

## Insulation characteristics

|                  |  |
|------------------|--|
| Protection class | I (Protective grounding of all conductive housing parts) |
|------------------|--|

## Insulation characteristics

|                      |  |
|----------------------|--|
| Overvoltage category | III (With protection modules plugged in) |
|                      | II (Without protection modules)          |
| Pollution degree     | 2  |

## Switch functions

|              |
|--------------|
| RMON History |
|--------------|

# SCX 2POE 2T - Industrial Ethernet Switch



1108544

<https://www.phoenixcontact.com/us/products/1108544>

|                      |   |
|----------------------|---|
| Diagnostic functions | LLDP (Link Layer Discovery Protocol)                                    |
|                      | SNMP traps  |
|                      | N:1-Portmirroring   |
|                      | ACD (Address Conflict Detection)  |
| Basic functions      | Store-and-forward switch, complies with IEEE 802.3                      |
| Filter functions     | Port prioritization   |
|                      | VLAN (up to 32 VLANs)   |
| IP parameterization  | DHCP client   |
|                      | BootP   |
|                      | Static IP address   |
| MAC address table    | 8k  |
| Management           | Web-based management (HTTP/HTTPS)                                       |
|                      | SNMPv2/v3   |
|                      | Command Line Interface (Telnet, SSH)                                    |
| Redundancy           | RSTP (Rapid Spanning Tree Protocol in accordance with IEEE 802.1D-2004) |
|                      | Large Tree Support  |
|                      | FRD (Fast Ring Detection)   |
| Additional functions | Jumbo frames  |
| Time synchronization | SNTP (Simple Network Time Protocol)                                     |

## Security functions

|                 |  |
|-----------------|--|
| Basic functions | Store-and-forward switch, complies with IEEE 802.3 |
|-----------------|--|

## Electrical properties

|                          |  |
|--------------------------|--|
| Rated insulation voltage | 3 kV AC (Input / output, IEC/EN 60950-1) |
|--------------------------|--|

## Supply

|                      |  |
|----------------------|--|
| Supply voltage range | 100 V AC ... 240 V AC -15 % ... +10 % (Single-phase) |
|----------------------|--|

## Connection data

### Supply

|   |   |
|---|---|
| Connection method   | Push-in spring connection                   |
| Conductor cross section flexible, with ferrule without plastic sleeve                     | 0.2 mm <sup>2</sup> ... 4 mm <sup>2</sup>   |
| Conductor cross section, flexible, with ferrule, with plastic sleeve                      | 0.2 mm <sup>2</sup> ... 4 mm <sup>2</sup>   |
| 2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve | 0.5 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> |
| Single conductor/terminal point, rigid  | 1 mm <sup>2</sup> ... 6 mm <sup>2</sup>     |
| Single-wire/terminal point, flexible  | 0.2 mm <sup>2</sup> ... 6 mm <sup>2</sup>   |
| Conductor cross section, flexible [AWG]   | 24 ... 10                                   |
| Stripping length  | 10.00 mm                                    |

## Environmental and real-life conditions

### Ambient conditions

# SCX 2POE 2T - Industrial Ethernet Switch



1108544

<https://www.phoenixcontact.com/us/products/1108544>

|   |  |
|---|--|
| Degree of protection                    | IP65 (in accordance with DIN EN 60529: Complete touch protection, dust cannot enter, spray water from any direction) |
| Impact strength                         | IK10 (in accordance with IEC 62262: Impact energy of 20 J, corresponds to 5 kg from a height of 40 cm)               |
| Ambient temperature (operation)         | -40 °C ... 70 °C (>50°C derating)  |
| Ambient temperature (storage/transport) | -40 °C ... 85 °C   |
| Altitude                                | 2000 m   |
| Permissible humidity (operation)        | 10 % ... 95 % (non-condensing)   |

## Standards and regulations

|                       |  |
|-----------------------|--|
| Other resistance      | UV-resistant in accordance with UL746C, f1 listing/rating (Outdoor housing, subject to 1,000 hour xenon weather testing, 7-day water submergence test) |
| Standards/regulations | IEC 62444  |
| Standard designation  | Strain relief  |
| Standards/regulations | IEC 61249-2-21   |
| Standard designation  | Halogen-free (housing, bromine: <900 ppm, chlorine: <900 ppm, total halogen content: <1,500 ppm)   |
| Standards/regulations | DIN EN 45545-2, requirement set R22, hazard level HL3  |
| Standard designation  | Fire protection  |

## Approvals

### CE

|             |              |
|-------------|--------------|
| Certificate | CE-compliant |
|-------------|--------------|

### UKCA

|             |                |
|-------------|----------------|
| Certificate | UKCA-compliant |
|-------------|----------------|

### UL, USA/Canada

|                |                              |
|----------------|------------------------------|
| Identification | Listed                       |
|                | UL 61010-1, 3rd Edition      |
|                | UL 61010-2-201, 2nd Edition  |
|                | CAN/CSA C22.2 No. 61010-1-12 |
|                | CSA C22.2 No. 61010-2-201:18 |

### Corrosive gas test

|                |                                  |
|----------------|----------------------------------|
| Identification | ISA-S71.04-1985 G3 Harsh Group A |
|----------------|----------------------------------|

## EMC data

|                               |  |
|-------------------------------|--|
| Noise immunity                | EN 61000-6-2   |
| Electromagnetic compatibility | Conformance with EMC Directive 2014/30/EU                              |
| Conducted noise emission      | EN 61000-6-3 Class B, domain of use: residential and small commercial  |
| Noise emission                | EN 61000-6-4, Class B, domain of use: residential and small commercial |

### Electrostatic discharge

|                       |              |
|-----------------------|--------------|
| Standards/regulations | EN 61000-4-2 |
|-----------------------|--------------|

# SCX 2POE 2T - Industrial Ethernet Switch



1108544

<https://www.phoenixcontact.com/us/products/1108544>

## Electrostatic discharge

|                    |             |
|--------------------|-------------|
| Contact discharge  | ± 6 kV      |
| Discharge in air   | ± 8 kV      |
| Indirect discharge | ± 6 kV      |
| Comments           | Criterion B |

## Electromagnetic HF field

|                       |              |
|-----------------------|--------------|
| Standards/regulations | EN 61000-4-3 |
|-----------------------|--------------|

## Electromagnetic HF field

|                 |  |
|-----------------|--|
| Frequency range | 80 MHz ... 3 GHz (80% amplitude modulation with 1 kHz) |
| Field intensity | 10 V/m   |
| Comments        | Criterion A  |

## Fast transients (burst)

|                       |              |
|-----------------------|--------------|
| Standards/regulations | EN 61000-4-4 |
|-----------------------|--------------|

## Fast transients (burst)

|          |                     |
|----------|---------------------|
| Input    | ± 2.2 kV (1 minute) |
| Signal   | ± 2.2 kV (1 minute) |
| Comments | Criterion B         |

## Surge current load (surge)

|                       |              |
|-----------------------|--------------|
| Standards/regulations | EN 61000-4-5 |
|-----------------------|--------------|

## Surge current load (surge)

|       |  |
|-------|--|
| Input | ± 1 kV (AC supply, line to line)<br>± 2 kV (AC supply, line to ground) |
|-------|--|

## Conducted interference

|                       |              |
|-----------------------|--------------|
| Standards/regulations | EN 61000-4-6 |
|-----------------------|--------------|

## Conducted interference

|                 |   |
|-----------------|---|
| Frequency range | 0.15 MHz ... 80 MHz (80% amplitude modulation with 1 kHz) |
| Comments        | Criterion A   |
| Voltage         | 10 V  |

## Emitted interference

|                       |  |
|-----------------------|--|
| Standards/regulations | EN 61000-6-4   |
| Comments              | Class B, domain of use: residential and small commercial |

## Criteria

|             |  |
|-------------|--|
| Criterion A | Normal operating behavior within the specified limits.                               |
| Criterion B | Temporary impairment to operational behavior that is corrected by the device itself. |

## System properties

### Functionality

# SCX 2POE 2T - Industrial Ethernet Switch



1108544

<https://www.phoenixcontact.com/us/products/1108544>

|                 |  |
|-----------------|--|
| Basic functions | Store-and-forward switch, complies with IEEE 802.3 |
|-----------------|--|

# SCX 2POE 2T - Industrial Ethernet Switch



1108544

<https://www.phoenixcontact.com/us/products/1108544>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27180590 |
| ECLASS-12.0 | 27180590 |
| ECLASS-13.0 | 27180590 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC000261 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 31261500 |
|-------------|----------|



# SCX 2POE 2T - Industrial Ethernet Switch



1108544

<https://www.phoenixcontact.com/us/products/1108544>

## Environmental product compliance

|            |                |
|------------|----------------|
| REACH SVHC | Lead 7439-92-1 |
|------------|----------------|

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)