# EV-T2M4CC-DC150A-8,0M35ESBK11 - DC charging cable



1192334

https://www.phoenixcontact.com/us/products/1192334

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



CHARX connect standard, DC charging cable, with vehicle charging connector and open cable end, for charging electric vehicles (EV) with direct current (DC), with connected PP contact, with replaceable mating face frame, with analog temperature sensors, CCS type 2, IEC 62196-3, 150 A / 1000 V (DC), PHOENIX CONTACT logo, cable: 8 m, black, straight, NOTE: Cable management may be required.

# Product description

DC charging cable with vehicle charging connector and free cable end for fast charging of electric vehicles (EV) with direct current (DC) via CCS type 2 vehicle charging inlets, for installation at charging stations for e-mobility (EVSE)

# Your advantages

- · Complete product range
- The right charging cable for every application, from the carport to the charging park
- · Convenient handling due to the ergonomic design
- · Available with your logo on request for consistent branding of your charging station
- · Developed and produced in accordance with the IATF 16949 automotive standard and ISO 9001

# Commercial data

Item number	1192334
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	EM01
Product key	XWBAAD
GTIN	4063151244262
Weight per piece (including packing)	11,446 g
Weight per piece (excluding packing)	11,410 g
Customs tariff number	85444290
Country of origin	PL



https://www.phoenixcontact.com/us/products/1192334

# Technical data

## **Product properties**

Product type	DC charging cable
Product family	CHARX connect standard
Application	for charging electric vehicles (EV) with direct current (DC)
	for installation at charging stations for electromobility (EVSE)
Туре	DC charging cable
	with vehicle charging connector and open cable end
Design	with connected PP contact
	with replaceable mating face frame
	with analog temperature sensors
Technology	Combined Charging System
Affixed logo	PHOENIX CONTACT logo
Label	14.1 mm x 44.8 mm (customer logo on request)
Charging standard	CCS type 2
Charging mode	Mode 4

#### **Electrical properties**

Type of signal transmission	Pulse width modulation with modulated Powerline communication in accordance with ISO/IEC 15118 / DIN SPEC 70121
Note on the connection method	Crimp connection, cannot be disconnected
Coding	1500 $\Omega$ (between PE and PP)
	PP signal contact connected to cable
Temperature monitoring	2x Pt 1000
Type of charging current	DC
Charging power	150 kW
Charging current	150 A

Power contact

Number	3 (PE, DC+, DC-)
Rated voltage	1000 V DC
Rated current	150 A (up to 40 °C)

#### Signal contact

Number	2 (CP, PP)
Rated voltage	30 V AC
Rated current	2 A
T	

 Temperature sensors (Pt 1000)

 Sensor type
 Pt 1000

 Standards/regulations
 DIN EN 60751

 Attachment point
 Sensor for the DC contacts

 Switch-off temperature
 90 °C ±1 K (equivalent to a Pt 1000 value of 1346.5 Ω)



https://www.phoenixcontact.com/us/products/1192334

Long-term stability	0.06 % (after 1000 hours at 130 °C)
Recommended measured current	1 mA (1 V at 0°C)
Coefficient	3850 ppm/K
Ambient temperature	-50 °C 130 °C (Operation)

## Dimensions

Vehicle charging connector

Width	75 mm
Height	139 mm
Depth	267 mm

## Material specifications

Color (Housing)	black (9005)
Color (Handle area)	gray (7042)
Color (Mating face)	black (9005)
Color (Protective cap)	black (9005)
Color (Cable)	black (9005)
Material (Vehicle charging connector)	Plastic
Material (Cable outer sheath)	TPE-U
Material (Contact surface)	Silver
Flammability rating according to UL 94	V0 (Mating face)

#### Cable/line

Cable length	8 m ±45 mm
Cable length	8 III 143 IIIII
Wiring standards/regulations	prEN 50620/DIN EN 50620
Cable weight	max. 1380.00 kg/km
Cable type	Class 6
Cable type	straight
Cable structure	2 x 35 mm² + 1 x 25 mm² + 3 x 2 x 0.75 mm²
External cable diameter	25.90 mm ±0.4 mm
Outer sheath, material	TPE-U
Stripping length of the sheath	140 mm ±10 mm
Stripping length	140 mm ±10 mm
Cable resistance	≤ 0.000554 Ω/m (based on a power core, at an ambient temperature of 20°C)
Bending radius	min. 259 mm (10x Ø)

# Mechanical properties

Mechanical data

Insertion/withdrawal cycles	> 10000
Insertion force	< 100 N
Withdrawal force	< 100 N

## Environmental and real-life conditions



https://www.phoenixcontact.com/us/products/1192334

Degree of protection (Vehicle charging connector)	IP44 (plugged in; when plugged in and ready to operate, the degree of protection is only ensued if both plug-in components are original products from Phoenix Contact or suitable standard compliant products)
Ambient temperature (operation)	-30 °C 40 °C
	max. 55 °C (Current reduction required, observe the DC contact temperature limit value of 90°C)
Ambient temperature (storage/transport)	-40 °C 80 °C
Altitude	5000 m (above sea level)
ndards and regulations	
-	NOTE: Cable management may be required.

#### Standards

Standards/regulations

IEC 62196-3



cable

https://www.phoenixcontact.com/us/products/1192334

# Classifications

## ECLASS

ECLASS-11.0	27144705
ECLASS-12.0	27144705
ECLASS-13.0	27144705

## ETIM

	ETIM 9.0	EC002897	
UNSPSC			
	UNSPSC 21.0	39121500	



https://www.phoenixcontact.com/us/products/1192334

# Environmental product compliance

REACh SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 10;
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com