

MACX MCR-1TS-I-OLP-SP - Temperature measuring transducer



1145196

<https://www.phoenixcontact.com/us/products/1145196>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Output loop-powered temperature transducer for transmitting RTD and TC sensor signals as well as from resistance and voltage sensors via 4 mA ... 20 mA. HART, Signal conditioner, Standard configuration, Push-in connection

Commercial data

Item number	1145196
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	NULL
Product key	CK1322
GTIN	4063151135713
Weight per piece (including packing)	157.4 g
Weight per piece (excluding packing)	152.1 g
Customs tariff number	85437090
Country of origin	DE

MACX MCR-1TS-I-OLP-SP - Temperature measuring transducer



1145196

<https://www.phoenixcontact.com/us/products/1145196>

Technical data

Product properties

Product type	Temperature transmitter
Product family	MACX Analog
No. of channels	1
Type	Signal conditioner
Configuration	Software
	HART

Insulation characteristics

Overvoltage category	II
Pollution degree	2

Electrical properties

Step response (0–99%)	1 s (TC)
	1 s (RTD)

Electrical isolation Input/output

Test voltage	2 kV AC (50 Hz, 60 s)
--------------	-----------------------

Supply

Supply voltage range	loop-powered, no external supply necessary
	11 V DC ... 36 V DC (Standard)

Input data

Signal

Input signal	Temperature
--------------	-------------

Measurement

Number of inputs	1
Input voltage range	-20 mV ... 100 mV (Minimum measuring span: 5 mV)
Sensor types (RTD) that can be used	Pt, Ni, Cu sensors: 2, 3, 4-wire
Sensor types that can be used (TC)	A, B, C, D, E, J, K, L, N, R, S, T, U
Temperature measuring range	-250 °C ... 2500 °C (Range depending on the sensor type)
Temperature measuring range	≥ 10 K (RTD)
	≥ 50 K (TC)
Linear resistance measuring range	10 Ω ... 2000 Ω (Minimum measuring span: 10 Ω)

Output data

Signal: Current

Current output signal	4 mA ... 20 mA
	20 mA ... 4 mA

MACX MCR-1TS-I-OLP-SP - Temperature measuring transducer



1145196

<https://www.phoenixcontact.com/us/products/1145196>

Max. current output signal	23 mA
Load	$(U_L - 11 \text{ V}) / 0,023 \text{ A}$
HART coding	FSK $\pm 0.5 \text{ mA}$
HART version	7
Transmission speed	1200 Baud
Mains frequency filter	50/60 Hz
Communication resistance	$\geq 250 \Omega$
Switch-on delay	$\approx \phi_s$ (HART) $\approx \phi_s$ (Measured value)

Connection data

Connection method	Push-in connection
Stripping length	8 mm
Conductor cross section rigid	0.2 mm ² ... 1.5 mm ²
Conductor cross section flexible	0.2 mm ² ... 1.5 mm ²
Conductor cross section AWG	24 ... 16

Ex data

Ex installation (EPL)	Gc Div. 2
-----------------------	--------------

Interfaces


Data communication (bypass)

Protocols supported	HART
---------------------	------

Signaling

Status display	LED red
----------------	---------

Dimensions

Dimensional drawing	
Width	12.5 mm
Height	116 mm
Depth	113.7 mm
Depth NS 35/7,5	114.5 mm (Snapped onto DIN rail NS 35/7,5 in accordance with EN 60715)

Material specifications

MACX MCR-1TS-I-OLP-SP - Temperature measuring transducer



1145196

<https://www.phoenixcontact.com/us/products/1145196>

Color	gray (RAL 7042)
-------	-----------------

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (storage/transport)	-50 °C ... 100 °C
Altitude	≤ 4000 m (Above sea level)
Climatic class	B2
Permissible humidity (operation)	5 % ... 95 % (non-condensing)

Approvals

CE

Certificate	CE-compliant
-------------	--------------

ATEX

Identification	⊕ II 3 G Ex ec IIC T6
Certificate	PxCIF20ATEX1145192U

CSA

Identification	Ex ec IIC T6...T4
----------------	-------------------

Mounting

Mounting type	DIN rail mounting
---------------	-------------------

MACX MCR-1TS-I-OLP-SP - Temperature measuring transducer



1145196

<https://www.phoenixcontact.com/us/products/1145196>

Classifications

ECLASS

ECLASS-11.0	27210129
ECLASS-12.0	27210129
ECLASS-13.0	27210129

ETIM

ETIM 9.0	EC002919
----------	----------

UNSPSC

UNSPSC 21.0	41112100
-------------	----------

MACX MCR-1TS-I-OLP-SP - Temperature measuring transducer



1145196

<https://www.phoenixcontact.com/us/products/1145196>

Environmental product compliance

China RoHS	Environmentally Friendly Use Period = 50 years For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"
------------	--

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com