

https://www.phoenixcontact.com/us/products/1190420



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



IP66 Touch panel with 12.1-inch widescreen (16:9) XGA, PCAP display, software: Visu+ RT

Your advantages

- · PCAP touch interface, ten-point multi touch control
- · Fanless design
- · Dual USB 2.0 ports
- · Integrated Visu+ visualization software
- · Ideal for use with PLCnext
- · Configurable multifunction serial port

Commercial data

Item number	1190420
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	DR17
Product key	DRCADC
GTIN	4063151239985
Weight per piece (including packing)	2,260 g
Weight per piece (excluding packing)	2,100 g
Customs tariff number	84714100
Country of origin	TW



https://www.phoenixcontact.com/us/products/1190420



Technical data

Product properties

Product type	Operator panel
Computer data	
Processor	Arm [®] Cortex [®] -A9, 800 MHz
Operating system	Windows [®] Embedded Compact 7
Data storage system	Flash eMMC, 8 GB
Slots	1x microSD
Display	
Display type	30.7 cm/12.1" TFT
Screen resolution	1280 x 800 Pixel(s) (WXGA)
Touch technology	projective-capacitive (PCAP)
Display lighting type	LED
Brightness	400 cd/m², typical (adjustable)
MTBF	50000 h
Color spectrum	16.7 million colors
Reading angle left	88.00 °
Reading angle right	88.00 °
Reading angle top	88.00 °
Reading angle bottom	88.00 °

Software

User software	Visu+
System requirements	
Runtime system	Visu+ Runtime

Interfaces

Interfaces	2x USB Host 2.0
	1x COM (RS-232/422/485)
Optional interfaces	Without optional interface
Network	1x Ethernet (10/100/1000 Mbps), RJ45
Bus system	without

System properties

User software	Visu+
System requirements	
Runtime system	Visu+ Runtime

Electrical properties

Supply



https://www.phoenixcontact.com/us/products/1190420



Supply voltage	24 V DC
Supply voltage range	18 V 32 V
Power supply unit	24 V DC ±20 %
Max. current consumption	1.81 A (max. system configuration at 24 V DC)
Typical current consumption	0.9 A (max. system configuration at 24 V DC)
Real-time clock	
Realtime clock	Integrated (battery backup)
ounting	
Mounting type	Front mounting
aterial specifications	
Material front plate	Aluminum (natural anodized)
Housing material	Aluminum cast alloy, powder-coated
onnection data Connection method	Screw connection
Conductor cross section, rigid	0.2 mm ² 2.5 mm ²
Conductor cross section, flexible	0.2 mm² 2.5 mm²
Conductor cross section AWG	24 12
Conductor cross section, flexible, with ferrule, with plastic sleeve	0.25 mm² 2.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve	0.25 mm² 2.5 mm²
Stripping length	7 mm
vironmental and real-life conditions	
Degree of protection	IP66 (front), IP20 (back)
Ambient temperature (operation)	-20 °C 50 °C
Ambient temperature (storage/transport)	-25 °C 85 °C
Permissible humidity (operation)	5 % 85 % (non-condensing)
Permissible humidity (storage/transport)	5 % 85 % (non-condensing)

Dimensions

Vibration (operation)

External dimensions	
Width / Height / Depth	302 mm / 229 mm / 51 mm (Dimensions of the front plate)
Installation dimensions	
Width / Height / Installation depth	292 mm / 219 mm / (Installation cutout)

1g



https://www.phoenixcontact.com/us/products/1190420



Classifications

ECLASS

	ECLASS-11.0	27330201
	ECLASS-12.0	27330201
	ECLASS-13.0	27330201
ETIN	M	
	ETIM 9.0	EC001412
LINIS	SPSC	

UNSPSC

UNSPSC 21.0 432119	00
--------------------	----



https://www.phoenixcontact.com/us/products/1190420



Environmental product compliance

REACh SVHC Lead 7439-92-1

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com