TP 6156-WHPS - Touch panel

1190421

https://www.phoenixcontact.com/us/products/1190421

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Your advantages

- · PCAP touch interface, ten-point multi touch control
- · Fanless design
- Dual USB 2.0 ports
- · Integrated Visu+ visualization software
- · Ideal for use with PLCnext
- · Configurable multifunction serial port

Commercial data

Item number	1190421
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	DR17
Product key	DRCADC
GTIN	4063151239053
Weight per piece (including packing)	2,260 g
Weight per piece (excluding packing)	2,100 g
Customs tariff number	84714100
Country of origin	TW

IP66 Touch panel with 15.6-inch widescreen (16:9) HD, PCAP display, Software: Visu+ RT

PHŒN

TP 6156-WHPS - Touch panel

1190421

https://www.phoenixcontact.com/us/products/1190421



Technical data

Product properties

Product type	Operator panel
Computer data	
Processor	Arm [®] Cortex [®] -A9, 800 MHz
Operating system	Windows [®] Embedded Compact 7
Data storage system	Flash eMMC, 8 GB
Slots	1x microSD
Display	
Display type	39.6 cm/15.6" TFT
Screen resolution	1920 x 1080 Pixel(s) (HD)
Touch technology	projective-capacitive (PCAP)
Display lighting type	LED
Brightness	450 cd/m ²
MTBF	50000 h
Color spectrum	16.7 million colors
Reading angle left	85.00 °
Reading angle right	85.00 °
Reading angle top	85.00 °
Reading angle bottom	85.00 °
oftware	
User software	Visu+
System requirements	
Runtime system	Visu+ Runtime
terfaces	
Interfaces	2x USB Host 2.0
interfaces	1x COM (RS-232/422/485)
Optional interfaces	Without optional interface
Network	1x Ethernet (10/100/1000 Mbps), RJ45
Bus system	without
ystem properties	
User software	Visu+
System requirements	
Runtime system	Visu+ Runtime

Electrical properties

TP 6156-WHPS - Touch panel

1190421

https://www.phoenixcontact.com/us/products/1190421



	Supply voltage	24 V DC
	Supply voltage range	18 V 32 V
	Power supply unit	24 V DC ±20 %
	Max. current consumption	1.81 A (max. system configuration at 24 V DC)
	Typical current consumption	1.27 A (max. system configuration at 24 V DC)
Real-time clock		
	Realtime clock	Integrated (battery backup)
Мо	unting	
	Mounting type	Front mounting
Ма	terial specifications	
	Material front plate	Aluminum (natural anodized)
	Housing material	Aluminum cast alloy, powder-coated
Со	nnection data	
	Connection method	Screw connection
	Conductor cross section, rigid	0.2 mm ² 2.5 mm ²
	Conductor cross section, flexible	0.2 mm ² 2.5 mm ²
	Conductor cross section AWG	24 12
	Conductor cross section, flexible, with ferrule, with plastic sleeve	0.25 mm ² 2.5 mm ²
	Conductor cross section flexible, with ferrule without plastic sleeve	0.25 mm ² 2.5 mm ²
	Stripping length	7 mm

Environmental and real-life conditions

 Ambient conditions

 Degree of protection
 IP66 (front), IP20 (back)

 Ambient temperature (operation)
 0 °C ... 50 °C

 Ambient temperature (storage/transport)
 -20 °C ... 60 °C

 Permissible humidity (operation)
 10 % ... 95 % (non-condensing)

 Permissible humidity (storage/transport)
 5 % ... 85 % (non-condensing)

 Vibration (operation)
 1g

Dimensions

External dimensions			
Width / Height / Depth	398 mm / 273 mm / 51 mm (Dimensions of the front plate)		
Installation dimensions			
Width / Height / Installation depth	388 mm / 263 mm / (Installation cutout)		



1190421

https://www.phoenixcontact.com/us/products/1190421



Classifications

ECLASS

ECLASS-12.0 27330201	
ECLASS-13.0 27330201	

ETIM

	ETIM 9.0	EC001412	
UNSPSC			
	UNSPSC 21.0	43211900	



1190421

https://www.phoenixcontact.com/us/products/1190421



Environmental product compliance

REACh SVHC

Lead 7439-92-1

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com