TP 6185-WHPS - Touch panel

1190423

https://www.phoenixcontact.com/us/products/1190423

PHŒNIX CONTACT

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

IP66 Touch panel with 18.5-inch widescreen (16:9) HD, PCAP display, Software: Visu+ RT



Your advantages

- · PCAP touch interface, ten-point multi touch control
- · Fanless design
- Dual USB 2.0 ports
- · Integrated Visu+ visualization software
- · Ideal for use with PLCnext
- · Configurable multifunction serial port

Commercial data

Item number	1190423
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	DR17
Product key	DRCADC
GTIN	4063151240042
Weight per piece (including packing)	2,260 g
Weight per piece (excluding packing)	99,999 g
Customs tariff number	84714100
Country of origin	TW



1190423

https://www.phoenixcontact.com/us/products/1190423



Technical data

Product properties

Product type	Operator panel
Computer data	
Processor	Arm [®] Cortex [®] -A9, 800 MHz
Operating system	Windows [®] Embedded Compact 7
Data storage system	Flash eMMC, 8 GB
Slots	1x microSD
Display	
Display type	46.9 cm/18.5" TFT
Screen resolution	1920 x 1080 Pixel(s) (HD)
Touch technology	projective-capacitive (PCAP)
Display lighting type	LED
Brightness	350 cd/m², typical (adjustable)
MTBF	50000 h
Color spectrum	16.7 million colors
Reading angle left	89.00 °
Reading angle right	89.00 °
Reading angle top	89.00 °
Reading angle bottom	89.00 °
oftware	
User software	Visu+
System requirements	
Runtime system	Visu+ Runtime
terfaces	
Interfaces	2x USB Host 2.0
Intenaces	1x COM (RS-232/422/485)
Optional interfaces	Without optional interface
Network	1x Ethernet (10/100/1000 Mbps), RJ45
Bus system	without
vstem properties	
User software	Visu+
System requirements	
Runtime system	Visu+ Runtime

Electrical properties

TP 6185-WHPS - Touch panel

1190423

https://www.phoenixcontact.com/us/products/1190423



Supply voltage range 18 V 32 V Power supply unit 24 V DC ±20 % Max. current consumption 1.81 A (max. system configuration at 24 V DC) Typical current consumption 1.34 A (max. system configuration at 24 V DC) Real-time clock Integrated (battery backup)	
Max. current consumption 1.81 A (max. system configuration at 24 V DC) Typical current consumption 1.34 A (max. system configuration at 24 V DC) Real-time clock Realtime clock	
Typical current consumption 1.34 A (max. system configuration at 24 V DC) Real-time clock Integrated (battery backup)	
Real-time clock Integrated (battery backup)	
Realtime clock Integrated (battery backup)	
Mounting	
-	
Mounting type Front mounting	
Material specifications	
Material front plate Aluminum (natural anodized)	
Housing material Aluminum cast alloy, powder-coated	
Connection data	
Connection method Screw connection	
Conductor cross section, rigid 0.2 mm ² 2.5 mm ²	
Conductor cross section, flexible 0.2 mm ² 2.5 mm ²	
Conductor cross section AWG 24 12	
Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm ² 2.5 mm ²	
Conductor cross section flexible, with ferrule without plastic 0.25 mm ² 2.5 mm ² sleeve	
Stripping length 7 mm	

Environmental and real-life conditions

 Ambient conditions

 Degree of protection
 IP66 (front), IP20 (back)

 Ambient temperature (operation)
 0 °C ... 50 °C

 Ambient temperature (storage/transport)
 -20 °C ... 60 °C

 Permissible humidity (operation)
 10 % ... 95 % (non-condensing)

 Permissible humidity (storage/transport)
 5 % ... 85 % (non-condensing)

 Vibration (operation)
 1g

Dimensions

External dimensions				
Width / Height / Depth	465 mm / 310 mm / 51 mm (Dimensions of the front plate)			
Installation dimensions				
Width / Height / Installation depth	455 mm / 300 mm / (Installation cutout)			



1190423

https://www.phoenixcontact.com/us/products/1190423



Classifications

ECLASS

ECLASS-12.0 27330201	
ECLASS-13.0 27330201	

ETIM

	ETIM 9.0	EC001412	
UNSPSC			
	UNSPSC 21.0	43211900	



1190423

https://www.phoenixcontact.com/us/products/1190423



Environmental product compliance

REACh SVHC

Lead 7439-92-1

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com