TP 6215-WHPS - Touch panel

1190424

https://www.phoenixcontact.com/us/products/1190424

PHŒNIX CONTACT

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

IP66 Touch panel with 21.5-inch widescreen (16:9) HD, PCAP display, Software: Visu+ RT



Your advantages

- · PCAP touch interface, ten-point multi touch control
- · Fanless design
- Dual USB 2.0 ports
- · Integrated Visu+ visualization software
- · Ideal for use with PLCnext
- · Configurable multifunction serial port

Commercial data

| Item number | 1190424 |
|--------------------------------------|--------------------------------|
| Packing unit | 1 pc |
| Note | Made to order (non-returnable) |
| Sales key | DR17 |
| Product key | DRCADC |
| GTIN | 4063151239992 |
| Weight per piece (including packing) | 2,260 g |
| Weight per piece (excluding packing) | 99,999 g |
| Customs tariff number | 84714100 |
| Country of origin | TW |



1190424

https://www.phoenixcontact.com/us/products/1190424



Technical data

Product properties

| Product type | Operator panel |
|---------------------------------------|---|
| Computer data | |
| Processor | Arm [®] Cortex [®] -A9, 800 MHz |
| Operating system | Windows [®] Embedded Compact 7 |
| Data storage system | Flash eMMC, 8 GB |
| Slots | 1x microSD |
| Display | |
| Display type | 54.6 cm / 21.5" TFT |
| Screen resolution | 1920 x 1080 Pixel(s) (HD) |
| Touch technology | projective-capacitive (PCAP) |
| Display lighting type | LED |
| Brightness | 400 cd/m², typical (adjustable) |
| MTBF | 50000 h |
| Color spectrum | 16.7 million colors |
| Reading angle left | 89.00 ° |
| Reading angle right | 89.00 ° |
| Reading angle top | 89.00 ° |
| Reading angle bottom | 89.00 ° |
| oftware | |
| User software | Visu+ |
| Sustem requiremente | |
| System requirements Runtime system | Visu+ Runtime |
| | |
| erfaces | |
| Interfaces | 2x USB Host 2.0 |
| | 1x COM (RS-232/422/485) |
| Optional interfaces | Without optional interface |
| Network | 1x Ethernet (10/100/1000 Mbps), RJ45 |
| Bus system | without |
| stem properties | |
| User software | Visu+ |
| System requirements | |
| Runtime system | Visu+ Runtime |

Electrical properties

TP 6215-WHPS - Touch panel

1190424

https://www.phoenixcontact.com/us/products/1190424



| Supply voltage range 18 V 32 V Power supply unit 24 V DC ±20 % Max. current consumption 1.81 A (max. system configuration at 24 V DC) Typical current consumption 1.37 A (max. system configuration at 24 V DC) Real-time clock Realtime clock Realtime clock Integrated (battery backup) | |
|---|--|
| Max. current consumption 1.81 A (max. system configuration at 24 V DC) Typical current consumption 1.37 A (max. system configuration at 24 V DC) Real-time clock Realtime clock | |
| Typical current consumption 1.37 A (max. system configuration at 24 V DC) Real-time clock Integrated (battery backup) | |
| Real-time clock Integrated (battery backup) | |
| Realtime clock Integrated (battery backup) | |
| | |
| Mounting | |
| | |
| Mounting type Front mounting | |
| Material specifications | |
| Material front plate Aluminum (natural anodized) | |
| Housing material Aluminum cast alloy, powder-coated | |
| Connection data | |
| Connection method Screw connection | |
| Conductor cross section, rigid 0.2 mm ² 2.5 mm ² | |
| Conductor cross section, flexible 0.2 mm ² 2.5 mm ² | |
| Conductor cross section AWG 24 12 | |
| Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm ² 2.5 mm ² | |
| Conductor cross section flexible, with ferrule without plastic 0.25 mm ² 2.5 mm ² sleeve | |
| Stripping length 7 mm | |

Environmental and real-life conditions

 Ambient conditions

 Degree of protection
 IP66 (front), IP20 (back)

 Ambient temperature (operation)
 0 °C ... 50 °C

 Ambient temperature (storage/transport)
 -20 °C ... 60 °C

 Permissible humidity (operation)
 10 % ... 95 % (non-condensing)

 Permissible humidity (storage/transport)
 5 % ... 85 % (non-condensing)

 Vibration (operation)
 1g

Dimensions

| External dimensions | | | |
|-------------------------------------|---|--|--|
| Width / Height / Depth | 532 mm / 346 mm / 51 mm (Dimensions of the front plate) | | |
| Installation dimensions | | | |
| Width / Height / Installation depth | 522 mm / 336 mm / (Installation cutout) | | |



1190424

https://www.phoenixcontact.com/us/products/1190424



Classifications

ECLASS

| ECLASS-12.0 27330201 | |
|----------------------|--|
| ECLASS-13.0 27330201 | |

ETIM

| | ETIM 9.0 | EC001412 | |
|--------|-------------|----------|--|
| UNSPSC | | | |
| | UNSPSC 21.0 | 43211900 | |



1190424

https://www.phoenixcontact.com/us/products/1190424



Environmental product compliance

REACh SVHC

Lead 7439-92-1

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com