

# PV-PRO/M/F-200/F-1500/3.7 - Fuse plug



1220814

<https://www.phoenixcontact.com/us/products/1220814>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Fuse plug, Range of articles: SUNCLIX, color: black, rated voltage: 1500 V DC (bis 4000m ü. NN), rated current: 3.7 A, Connection method: SUNCLIX PV connector. SUNCLIX fuse element for protecting panels and devices in photovoltaic systems

## Commercial data

Item number	1220814
Packing unit	8 pc
Minimum order quantity	8 pc
Note	Made to order (non-returnable)
Sales key	AB02
Product key	ABLBEA
GTIN	4063151308209
Weight per piece (including packing)	22.22 g
Weight per piece (excluding packing)	135.873 g
Customs tariff number	85354000
Country of origin	PL

## Technical data

### Notes

General	SUNCLIX fuse element for protecting panels and devices in photovoltaic systems
---------	--

### Product properties

Product type	Fuse
Product family	SUNCLIX

### Insulation characteristics

Protection class	II
Degree of pollution	2

### Electrical properties

Rated voltage (III/2)	1500 V
Nominal voltage ATD	1500 V DC (bis 4000m ü. NN)
Rated surge voltage	16 kV
Fuse adapter nominal current	3.7 A DC (Nominal current of the item)
Fuse-link nominal current	3.5 A DC (Nominal current of the fuse-link)

### Connection data

Connection method	SUNCLIX PV connector
-------------------	----------------------

### Material specifications

Color	black
Flammability rating according to UL 94	V0

### Cable/line

Cable type	H1Z2Z2-K
------------	----------

### Mechanical properties

#### Mechanical data

Insertion force	45 N ±10 N
Withdrawal force	250 N ±100 N

### Environmental and real-life conditions

#### Ambient conditions

Degree of protection	IP66 / IP68 (2 m / 24 h)
Ambient temperature (operation)	-40 °C ... 65 °C (Deviating ambient temperatures possible depending on the current carrying capacity/derating curve)
Ambient temperature (assembly)	-25 °C ... 50 °C

### Standards and regulations

# PV-PRO/M/F-200/F-1500/3.7 - Fuse plug



1220814

<https://www.phoenixcontact.com/us/products/1220814>

Standards/specifications	2 PfG 2380-2014-02
Note	in progress

# PV-PRO/M/F-200/F-1500/3.7 - Fuse plug



1220814

<https://www.phoenixcontact.com/us/products/1220814>

## Classifications

### ECLASS

ECLASS-11.0	27440190
ECLASS-12.0	27440190
ECLASS-13.0	27440190

### ETIM

ETIM 9.0	EC002943
----------	----------

### UNSPSC

UNSPSC 21.0	39121400
-------------	----------

# PV-PRO/M/F-200/F-1500/3.7 - Fuse plug



1220814

<https://www.phoenixcontact.com/us/products/1220814>

## Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e No hazardous substances above threshold values
------------	---

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)