

WP 6070-WVPS - Web panel



1290800

<https://www.phoenixcontact.com/us/products/1290800>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

IP66 Touch panel with 7.0-inch widescreen (16:9) VGA, PCAP display, Software: Qt Browser



Your advantages

- Easy startup – just enter the IP and URL
- Flexible, thanks to open web standard and free choice of web server and visualization software
- No security updates are required for JAVA or Flash plug-ins thanks to HTML5
- Ideal for use with PLCnext Engineer or CODESYS
- Embedded Linux operating system
- Visualization of self-programmed JavaScript applications possible

Commercial data

| | |
|--------------------------------------|--------------------------------|
| Item number | 1290800 |
| Packing unit | 1 pc |
| Note | Made to order (non-returnable) |
| Sales key | DR17 |
| Product key | DRCADF |
| GTIN | 4063151522568 |
| Weight per piece (including packing) | 2,260 g |
| Weight per piece (excluding packing) | 2,100 g |
| Customs tariff number | 84714100 |
| Country of origin | TW |

Technical data

Product properties

| | |
|--------------|----------------|
| Product type | Operator panel |
|--------------|----------------|

Computer data

| | |
|---------------------|---------------------------|
| Processor | Arm® Cortex®-A53, 1.6 GHz |
| Operating system | Yocto/Linux® |
| Data storage system | Flash eMMC, 8 GB |
| Slots | 1x microSD |

Display

| | |
|-----------------------|--------------------------------|
| Display type | 17.8 cm / 7"-TFT |
| Screen resolution | 800 x 480 Pixel(s) (WVGA) |
| Touch technology | projective-capacitive (PCAP) |
| Display lighting type | LED |
| Brightness | 500 cd/m² typical (adjustable) |
| MTBF | 50000 h |
| Color spectrum | 16.7 million colors |
| Reading angle left | 89.00 ° |
| Reading angle right | 89.00 ° |
| Reading angle top | 89.00 ° |
| Reading angle bottom | 89.00 ° |

Software

| | |
|---------------|------------|
| User software | QT browser |
|---------------|------------|

System requirements

| | |
|----------------|------------|
| Runtime system | Qt Browser |
|----------------|------------|

Interfaces

| | |
|---------------------|--------------------------------------|
| Interfaces | 2x USB Host 2.0, 1x USB Type C 3.0 |
| | 1x COM (RS-232/422/485) |
| Optional interfaces | Without optional interface |
| Network | 1x Ethernet (10/100/1000 Mbps), RJ45 |
| Bus system | without |

System properties

| | |
|---------------|------------|
| User software | QT browser |
|---------------|------------|

System requirements

| | |
|----------------|------------|
| Runtime system | Qt Browser |
|----------------|------------|

Electrical properties

Supply

WP 6070-WVPS - Web panel



1290800

<https://www.phoenixcontact.com/us/products/1290800>

| | |
|-----------------------------|--------------------|
| Supply voltage | 24 V DC |
| Supply voltage range | 18 V ... 32 V |
| Power supply unit | 24 V DC \pm 20 % |
| Max. current consumption | 1.81 A (24 V DC) |
| Typical current consumption | 0.61 A (24 V DC) |

Real-time clock

| | |
|----------------|-----------------------------|
| Realtime clock | Integrated (battery backup) |
|----------------|-----------------------------|

Mounting

| | |
|---------------|----------------|
| Mounting type | Front mounting |
|---------------|----------------|

Material specifications

| | |
|----------------------|------------------------------------|
| Material front plate | Aluminum (natural anodized) |
| Housing material | Aluminum cast alloy, powder-coated |

Connection data

| | |
|-----------------------------------|---|
| Connection method | Screw connection |
| Conductor cross section, rigid | 0.2 mm ² ... 2.5 mm ² |
| Conductor cross section, flexible | 0.2 mm ² ... 2.5 mm ² |
| Conductor cross section AWG | 24 ... 12 |
| Stripping length | 7 mm |

Environmental and real-life conditions

Ambient conditions

| | |
|--|-------------------------------|
| Degree of protection | IP66 (front), IP20 (back) |
| Ambient temperature (operation) | -20 °C ... 50 °C |
| Ambient temperature (storage/transport) | -25 °C ... 60 °C |
| Permissible humidity (operation) | 5 % ... 85 % (non-condensing) |
| Permissible humidity (storage/transport) | 5 % ... 85 % (non-condensing) |
| Vibration (operation) | 1g |

Dimensions

External dimensions

| | |
|------------------------|---|
| Width / Height / Depth | 202 mm / 146 mm / 51 mm (Dimensions of the front plate) |
|------------------------|---|

Installation dimensions

| | |
|-------------------------------------|---|
| Width / Height / Installation depth | 195 mm / 139 mm / (Installation cutout) |
|-------------------------------------|---|

1290800

<https://www.phoenixcontact.com/us/products/1290800>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27330201 |
| ECLASS-12.0 | 27330201 |
| ECLASS-13.0 | 27330201 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC001412 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 43211900 |
|-------------|----------|

WP 6070-WVPS - Web panel

1290800

<https://www.phoenixcontact.com/us/products/1290800>



Environmental product compliance

REACH SVHC

Lead 7439-92-1

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com