WP 6215-WHPS - Web panel

1290809

https://www.phoenixcontact.com/us/products/1290809

PHŒNIX CONTACT

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



IP66 Touch panel with 21.5-inch widescreen (16:9) HD, PCAP display, Software: Qt Browser

Your advantages

- · Easy startup just enter the IP and URL
- · Flexible, thanks to open web standard and free choice of web server and visualization software
- · No security updates are required for JAVA or Flash plug-ins thanks to HTML5
- · Ideal for use with PLCnext Engineer or CODESYS
- Embedded Linux operating system
- Visualization of self-programmed JavaScript applications possible

Commercial data

Item number	1290809
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	DR17
Product key	DRCADF
GTIN	4063151523138
Weight per piece (including packing)	2,260 g
Weight per piece (excluding packing)	2,100 g
Customs tariff number	84714100
Country of origin	TW

WP 6215-WHPS - Web panel

1290809

https://www.phoenixcontact.com/us/products/1290809



Technical data

Product properties

Product type	Operator panel
Computer data	
Processor	Arm [®] Cortex [®] -A53, 1.6 GHz
Operating system	Yocto/Linux [®]
Data storage system	Flash eMMC, 8 GB
Slots	1x microSD
Display	
Display type	54.6 cm / 21.5" TFT
Screen resolution	1920 x 1080 Pixel(s) (Full HD)
Touch technology	projective-capacitive (PCAP)
Display lighting type	LED
Brightness	400 cd/m², typical (adjustable)
MTBF	50000 h
Color spectrum	16.7 million colors
Reading angle left	89.00 °
Reading angle right	89.00 °
Reading angle top	89.00 °
Reading angle bottom	89.00 °
ftware	
User software	QT browser
System requirements	
Runtime system	Qt Browser
erfaces	
Interfaces	2x USB Host 2.0, 1x USB Type C 3.0
	1x COM (RS-232/422/485)
Optional interfaces	Without optional interface
Network	1x Ethernet (10/100/1000 Mbps), RJ45
Bus system	without
stem properties	
User software	QT browser
System requirements	
Runtime system	Qt Browser

Electrical properties

WP 6215-WHPS - Web panel

1290809

https://www.phoenixcontact.com/us/products/1290809



Supply voltage	24 V DC
Supply voltage range	18 V 32 V
Power supply unit	24 V DC ±20 %
Max. current consumption	1.81 A (24 V DC)
Typical current consumption	1.37 A (24 V DC)
Real-time clock	
Realtime clock	Integrated (battery backup)
Mounting	
Mounting type	Front mounting
Material specifications	
Material front plate	Aluminum (natural anodized)
Housing material	Aluminum cast alloy, powder-coated
Connection data	
Connection method	Screw connection
Conductor cross section, rigid	0.2 mm ² 2.5 mm ²
Conductor cross section, flexible	0.2 mm ² 2.5 mm ²
Conductor cross section AWG	24 12
Stripping length	7 mm
Environmental and real-life conditions	
Ambient conditions	
Degree of protection	0 °C 50 °C
Ambient temperature (operation)	-20 °C 60 °C
Ambient temperature (storage/transport)	
Permissible humidity (operation)	10 % 95 % (non-condensing) 10 % 95 % (non-condensing)
Permissible humidity (storage/transport)	
Vibration (operation)	1g

Dimensions

External dimensions				
Width / Height / Depth	532 mm / 346 mm / 51 mm (Dimensions of the front plate)			
Installation dimensions				
Width / Height / Installation depth	522 mm / 336 mm / (Installation cutout)			



1290809

https://www.phoenixcontact.com/us/products/1290809



Classifications

ECLASS

ECLASS-11.0	27330201
ECLASS-12.0	27330201
ECLASS-13.0	27330201

ETIM

	ETIM 9.0	EC001412	
UNSPSC			
	UNSPSC 21.0	43211900	



1290809

https://www.phoenixcontact.com/us/products/1290809



Environmental product compliance

REACh SVHC

Lead 7439-92-1

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com