

1322610

https://www.phoenixcontact.com/us/products/1322610

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



CHARX connect modular, Cable set for infrastructure charging socket, Accessories, with slip-on sleeve at one end, Only for connection to generation 2 infrastructure charging sockets from Phoenix Contact, Type 2, IEC 62196-2, 32 A / 250 V (AC), Single wires, length: 1.5 m, Plug-in mounting

Product description

Cables with slip-on sleeves on one end for connection to infrastructure charging sockets, for charging electric vehicles (EV) with alternating current (AC), for installation in charging stations for electromobility (EVSE)

Your advantages

- · Protected against overheating with precise temperature measurement
- · Flexible mounting and easy maintenance with plug-in cables
- · Available with your logo on request for consistent branding of your charging station
- · Waterproof and dirtproof due to fully molded contacts
- Developed and produced in accordance with the IATF 16949 automotive standard and ISO 9001
- · Uniform, space-saving installation space

Commercial data

Item number	1322610
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	XWBAFC
GTIN	4063151674496
Weight per piece (including packing)	308 g
Weight per piece (excluding packing)	308 g
Country of origin	DE



1322610

https://www.phoenixcontact.com/us/products/1322610

Technical data

Product properties

Product type	Cable set for infrastructure charging socket
Product family	CHARX connect modular
Application	Only for connection to generation 2 infrastructure charging sockets from Phoenix Contact
Туре	Accessories
Design	with slip-on sleeve at one end
Charging standard	Type 2
Charging mode	Mode 3, Case B

Electrical properties

Note on the connection method	Plug-in connection, separable
Type of charging current	AC single-phase
Charging power rating	7.4 kW
Charging power	8 kW
Charging current	32 A

Power contact

Number	3 (L1, N, PE)
Rated voltage	250 V AC
Rated current	32 A AC

Signal contact

Number	2 (CP, PP)
Rated voltage	30 V AC
Rated current	2 A

Material specifications

Material (Contact surface)	Silver
----------------------------	--------

Cable/line

Cable length	1.5 m
Cable type	Single wires
Cable structure	3 x 6.0 mm ² + 2 x 0.5 mm ²

Single-core wires for AC

Cable length	1.5 m
Cable structure	3 x 6 mm²

Single-core wires for communication

Cable length	1.5 m
Cable structure	2 x 0.5 mm²



1322610

https://www.phoenixcontact.com/us/products/1322610

Mechanical properties

∖∕۱∟∩	hanical	l data

Insertion/withdrawal cycles	< 3

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-30 °C 50 °C
Ambient temperature (storage/transport)	-40 °C 80 °C
Altitude	5000 m (above sea level)

Standards and regulations

Standards

Standards/regulations	IEC 62196-2
-----------------------	-------------

Mounting



1322610

https://www.phoenixcontact.com/us/products/1322610

Classifications

ECLASS

201.00				
	ECLASS-11.0	27144792		
	ECLASS-12.0	27144792		
	ECLASS-13.0	27144792		
ETIM				
	ETIM 9.0	EC002884		
UNSPSC				
	UNSPSC 21.0	39121500		



1322610

https://www.phoenixcontact.com/us/products/1322610

Environmental product compliance

China RoHS	Environmentally Friendly Use Period = 10;
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com