

# CHARX T2HBI12-3AC32DC250-5,0M2 - Vehicle charging inlet



1338230

<https://www.phoenixcontact.com/us/products/1338230>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



CHARX connect universal, Vehicle charging inlet, for charging with alternating current (AC) and with direct current (DC), CCS type 2, IEC 62196-2, IEC 62196-3, 250 A / 1000 V (DC), 32 A / 480 V (AC), Single wires, length: 5 m, locking actuator: 12 V, 4-pos., Front and rear mounting, M6, housing: black, A protective cap is supplied as standard for the DC and AC contacts.

## Product description

Vehicle charging inlet for charging with direct current (DC), compatible with type 2 CCS vehicle charging connectors (EVSE), for installation in electric vehicles (EV).

## Your advantages

- Complete product range
- Uniform, space-saving dimensions for the installation space and the screw connection points of all Phoenix Contact vehicle charging inlets
- Developed and produced in accordance with the IATF 16949 automotive standard and ISO 9001
- Integrated interlock during charging
- Manual emergency release of the locking actuator
- Protected and sealed against dirt and water with a high degree of protection

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 1338230       |
| Packing unit                         | 1 pc          |
| Minimum order quantity               | 1 pc          |
| Product key                          | XWCAID        |
| GTIN                                 | 4063151641399 |
| Weight per piece (including packing) | 16,485 g      |
| Weight per piece (excluding packing) | 16,485 g      |
| Country of origin                    | PL            |

# CHARX T2HBI12-3AC32DC250-5,0M2 - Vehicle charging inlet



1338230

<https://www.phoenixcontact.com/us/products/1338230>

## Technical data

### Notes

|         |  |
|---------|--|
| General | A protective cap is supplied as standard for the DC and AC contacts. |
|---------|--|

### Product properties

|                   |   |
|-------------------|---|
| Product type      | Vehicle charging inlet  |
| Product family    | CHARX connect universal   |
| Application       | for charging with alternating current (AC) and with direct current (DC)<br>for installation in electric vehicles (EV) |
| Technology        | Combined Charging System  |
| Charging standard | CCS type 2  |
| Charging mode     | Mode 2, 3, 4  |

### Electrical properties

|                               |  |
|-------------------------------|--|
| Type of signal transmission   | Pulse width modulation with modulated Powerline communication in accordance with ISO/IEC 15118 / DIN SPEC 70121                                    |
| Note on the connection method | Crimp connection, cannot be disconnected   |
| Insulation resistance         | > 200 MΩ   |
| Coding                        | 4.7 kΩ (between PE and PP)   |
| Temperature measurement       | DC contacts: 2x PT1000 (DIN EN 60751)  |
| Temperature monitoring        | AC contacts: PTC chain (DIN EN 60738-1)  |
| Type of charging current      | AC 3-phase   |
| Charging power                | 26.6 kW  |
| Charging current              | 32 A   |
| Type of charging current      | DC   |
| Charging power                | 250 kW   |
| Charging current              | 250 A  |
| Type of charging current      | DC Boost Mode  |
| Charging power                | up to 500 kW (Boost Mode, depending on the ambient conditions. For detailed information, see the packing slip in the download area for this item.) |
| Charging current              | up to 500 A (Boost Mode, depending on the ambient conditions. For detailed information, see the packing slip in the download area for this item.)  |

### Power contact

|               |                                 |
|---------------|---------------------------------|
| Number        | 7 (L1, L2, L3, N, PE, DC+, DC-) |
| Rated voltage | 480 V AC<br>1000 V DC           |
| Rated current | 32 A AC<br>250 A DC             |

### Signal contact

# CHARX T2HBI12-3AC32DC250-5,0M2 - Vehicle charging inlet



1338230

<https://www.phoenixcontact.com/us/products/1338230>

|               |            |
|---------------|------------|
| Number        | 2 (CP, PP) |
| Rated voltage | 30 V AC    |
| Rated current | 2 A        |

## Temperature sensors (PTC chain)

|                              |                                      |
|------------------------------|--------------------------------------|
| Sensor type                  | PTC chain                            |
| Standards/regulations        | DIN EN 60738-1                       |
| Attachment point             | Sensor for the AC contacts           |
| Measuring range_resistance   | 790.00 $\Omega$ ... 1420.00 $\Omega$ |
| Resistance                   | max. 1280 $\Omega$ $\pm$ 5 K         |
| Recommended measured current | $\leq$ 1 mA ( $U_{max}$ = 16 V DC)   |
| Ambient temperature          | -40 °C ... 130 °C (Operation)        |

## Temperature sensors (Pt 1000)

|                       |                               |
|-----------------------|-------------------------------|
| Sensor type           | Pt 1000                       |
| Standards/regulations | DIN EN 60751                  |
| Attachment point      | 2 sensors for the DC contacts |

## Locking actuator

|                                  |            |
|----------------------------------|------------|
| Operating voltage                | 12 V       |
| Note number of positions         | 4-pos.     |
| Position of the locking actuator | right-side |

## Locking actuator

|  |                     |
|--|---------------------|
| Operating voltage                        | 12 V                |
| Note number of positions                 | 4-pos.              |
| Position of the locking actuator         | right-side          |
| Possible power supply range at the motor | 9 V ... 16 V        |
| Maximum voltage for locking detection    | 12 V                |
| Typical motor current for locking        | 0.25 A              |
| Reverse current of the motor             | max. 1.5 A          |
| Max. dwell time with reverse current     | 1 s                 |
| Recommended adaptation time              | 600 ms              |
| Pause time after entry or exit path      | 3 s                 |
| Service life insertion cycles            | > 10000 load cycles |
| Lock recognition                         | available           |
| Mechanical emergency release             | available           |
| Ambient temperature (operation)          | -40 °C ... 80 °C    |

## Dimensions

|        |           |
|--------|-----------|
| Width  | 117.65 mm |
| Height | 90 mm     |
| Depth  | 117.65 mm |

## Material specifications

|                 |              |
|-----------------|--------------|
| Color (Housing) | black (9005) |
|-----------------|--------------|

# CHARX T2HBI12-3AC32DC250-5,0M2 - Vehicle charging inlet



1338230

<https://www.phoenixcontact.com/us/products/1338230>

|                            |              |
|----------------------------|--------------|
| Color (Mating face)        | black (9005) |
| Material (Housing)         | Plastic      |
| Material (Contact surface) | Silver       |

## Cable/line

|                            |                       |
|----------------------------|-----------------------|
| Cable length               | 5 m                   |
| Cable type                 | Single wires          |
| Single wire, cross section | 95.00 mm <sup>2</sup> |

### Single-core wires for AC

|                         |                       |
|-------------------------|-----------------------|
| Cable length            | 5 m                   |
| Cable structure         | 4 x 6 mm <sup>2</sup> |
| Single wire, material   | Silicone              |
| Single wire, color      | OG                    |
| External cable diameter | 14.70 mm ±0.2 mm      |
| Cable resistance        | ≤ 3.2 Ω/km            |

### Single-core wires for DC

|                         |                        |
|-------------------------|------------------------|
| Cable length            | 5 m                    |
| Cable structure         | 2 x 95 mm <sup>2</sup> |
| Single wire, material   | Silicone               |
| Single wire, color      | OG                     |
| External cable diameter | 20.60 mm ±0.3 mm       |
| Cable resistance        | ≤ 0.196 Ω/km           |

### Single-core wire for PE

|                         |                        |
|-------------------------|------------------------|
| Cable length            | 5 m                    |
| Cable structure         | 1 x 25 mm <sup>2</sup> |
| Single wire, material   | Silicone               |
| Single wire, color      | GN/YE                  |
| External cable diameter | 8.60 mm ±0.1 mm        |
| Cable resistance        | ≤ 0.743 Ω/km           |

### Single-core wires for locking actuator

|                         |                            |
|-------------------------|----------------------------|
| Cable length            | 1.5 m                      |
| Cable structure         | 4 x 0.5 mm <sup>2</sup>    |
| Single wire, material   | PVC                        |
| Single wire, color      | BU/RD, BU/GN, BU/YE, BU/BN |
| External cable diameter | 1.60 mm ±0.20 mm           |
| Cable resistance        | ≤ 37.1 Ω/m                 |

### Single-core wires for PTC temperature sensors

|                       |                         |
|-----------------------|-------------------------|
| Cable length          | 1 m                     |
| Cable structure       | 5 x 0,5 mm <sup>2</sup> |
| Single wire, material | PVC                     |
| Single wire, color    | BN/GY                   |

# CHARX T2HBI12-3AC32DC250-5,0M2 - Vehicle charging inlet



1338230

<https://www.phoenixcontact.com/us/products/1338230>

|                         |                  |
|-------------------------|------------------|
|                         | BN/YE/GN         |
| External cable diameter | 1.60 mm ±0.20 mm |
| Cable resistance        | ≤ 37.1 Ω/m       |

## Single-core wires for Pt 1000 temperature sensors

|                         |                         |
|-------------------------|-------------------------|
| Cable length            | 1 m                     |
| Cable structure         | 3 x 0.5 mm <sup>2</sup> |
| Single wire, material   | PVC                     |
| Single wire, color      | BN<br>GN<br>YE          |
| External cable diameter | 1.60 mm ±0.20 mm        |
| Cable resistance        | ≤ 37.1 Ω/m              |

## Single-core wires for communication

|                         |                         |
|-------------------------|-------------------------|
| Cable length            | 1 m                     |
| Cable structure         | 2 x 0.5 mm <sup>2</sup> |
| Single wire, material   | PVC                     |
| Single wire, color      | BK<br>WH                |
| External cable diameter | 1.60 mm ±0.20 mm        |
| Cable resistance        | ≤ 37.1 Ω/m              |

## Mechanical properties

### Mechanical data

|                             |         |
|-----------------------------|---------|
| Insertion/withdrawal cycles | > 10000 |
| Insertion force             | < 100 N |
| Withdrawal force            | < 100 N |

## Environmental and real-life conditions

### Ambient conditions

|   |   |
|---|---|
| Degree of protection (Vehicle charging inlet) | IP55 (plugged in; when plugged in and ready to operate, the degree of protection is only ensued if both plug-in components are original products from Phoenix Contact or suitable standard-compliant products)<br>IP67 (Inner area of vehicle charging inlet) |
| Ambient temperature (operation)               | -40 °C ... 60 °C  |
| Ambient temperature (storage/transport)       | -40 °C ... 85 °C  |
| Altitude                                      | 4000 m (above sea level)  |

## Standards and regulations

### Standards

|                       |                            |
|-----------------------|----------------------------|
| Standards/regulations | IEC 62196-2<br>IEC 62196-3 |
|-----------------------|----------------------------|

# CHARX T2HBI12-3AC32DC250-5,0M2 - Vehicle charging inlet



1338230

<https://www.phoenixcontact.com/us/products/1338230>

## Mounting

|  |   |
|--|---|
| Mounting type                            | Front and rear mounting (0 to 90 degree frontal inclination possible) |
| Mounting hole diameter                   | 6.70 mm (ø)   |
| Fixing screws                            | M6  |
| Screws included in the scope of delivery | none  |

# CHARX T2HBI12-3AC32DC250-5,0M2 - Vehicle charging inlet



1338230

<https://www.phoenixcontact.com/us/products/1338230>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27144706 |
| ECLASS-12.0 | 27144706 |
| ECLASS-13.0 | 27144706 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC002898 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121800 |
|-------------|----------|

# CHARX T2HBI12-3AC32DC250-5,0M2 - Vehicle charging inlet



1338230

<https://www.phoenixcontact.com/us/products/1338230>

## Environmental product compliance

|            |  |
|------------|--|
| REACH SVHC | Lead 7439-92-1   |
|            | DOTe 15571-58-1  |
|            | Dechlorane Plus  |
| China RoHS | Environmentally Friendly Use Period = 10;  |
|            | For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads" |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)