

SAC-5P-MR/ 2,0-924 SCO - Bus system cable



1405978

<https://www.phoenixcontact.com/us/products/1405978>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Bus system cable, CANopen[®], DeviceNet[™], 5-position, PVC, gray, shielded (Plastic-coated aluminum foil with a filler litz wire, aluminum side outside), Plug angled M12, coding: A, on free cable end, cable length: 2 m, Connector unshielded

Commercial data

| | |
|--------------------------------------|---------------|
| Item number | 1405978 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | BF15 |
| Product key | BF1IHE |
| GTIN | 4046356800501 |
| Weight per piece (including packing) | 138.3 g |
| Weight per piece (excluding packing) | 138.3 g |
| Customs tariff number | 85444290 |
| Country of origin | US |

SAC-5P-MR/ 2,0-924 SCO - Bus system cable



1405978

<https://www.phoenixcontact.com/us/products/1405978>

Technical data

Product properties

| | |
|----------------------|-------------------------|
| Product type | Data cable preassembled |
| Sensor type | CANopen [®] |
| Number of positions | 5 |
| Application | Standard, U.S. cables |
| No. of cable outlets | 1 |
| Shielded | yes |
| Coding | A |

Insulation characteristics

| | |
|----------------------|----|
| Overvoltage category | II |
| Degree of pollution | 3 |

Interfaces

| | |
|----------------------|--|
| Bus system | CANopen [®] /DeviceNet [™] |
| Signal type/category | CANopen [®] DeviceNet [™] |

Signaling

| | |
|------------------------|----|
| Status display | No |
| Status display present | No |

Electrical properties

| | |
|--------------------------------|--------------------|
| Insulation resistance | ≥ 100 MΩ |
| Nominal voltage U _N | 48 V AC 60 V DC |
| Nominal current I _N | 4 A |
| Transmission medium | Copper |

Material specifications

| | |
|--|---|
| Flammability rating according to UL 94 | HB |
| Material of grip body | TPU, hardly inflammable, self-extinguishing |
| Contact material | CuSn |
| Contact surface material | Ni/Au |
| Contact carrier material | TPU GF |
| Material for screw connection | Zinc die-cast, nickel-plated |

Connector

Connection 1

| | |
|---------------------|-----------------|
| Type | Plug angled M12 |
| Number of positions | 5 |
| Coding type | A (Standard) |

SAC-5P-MR/ 2,0-924 SCO - Bus system cable



1405978

<https://www.phoenixcontact.com/us/products/1405978>


Connection 2

| | |
|------|----------------|
| Type | free cable end |
|------|----------------|

Cable/line

| | |
|--------------|-----|
| Cable length | 2 m |
|--------------|-----|

CANopen[®]/DeviceNet[™], PVC, gray [924]

| | |
|---|--|
| Dimensional drawing |  |
| Cable weight | 64.51 kg/km |
| UL AWM Style | 2464 (80°C/300 V) |
| Number of positions | 4 |
| Shielded | yes |
| Cable type | CANopen [®] /DeviceNet [™] , PVC, gray [924] |
| Conductor structure | 2xAWG22 (Signal) + 2xAWG22 (Power) |
| Signal runtime | 4.46 ns/m |
| Conductor structure signal line | 19x 0.15 mm |
| AWG signal line | 22 |
| Conductor cross section | 2x 0.34 mm ² (Signal line) 2x 0.34 mm ² (Power supply) |
| Wire diameter incl. insulation | 1.27 mm ±0.05 mm (Signal line) 2.24 mm ±0.13 mm (Power supply) |
| External cable diameter | 6.90 mm ±0.13 mm |
| Outer sheath, material | PVC |
| External sheath, color | gray |
| Conductor material | Bare Cu litz wires |
| Material wire insulation | Foamed PE (Signal line) PVC (Power supply) |
| Single wire, color | red-black, blue-white |
| Twisted pairs | 2 cores to the pair |
| Type of pair shielding | Plastic-coated aluminum foil, aluminum side inside |
| Overall twist | 2 pairs around a drain wire in the center to the core |
| Insulation resistance | ≥ 59.38 Ω*m (Signal line) ≥ 57.41 GΩ*km (Power supply) |
| Wave impedance | 120 Ω ±12 Ω |
| Working capacitance | nom. 78.74 pF (per meter) |
| Minimum bending radius, flexible installation | 15 x D |
| Smallest bending radius, movable installation | 104 mm |

SAC-5P-MR/ 2,0-924 SCO - Bus system cable



1405978

<https://www.phoenixcontact.com/us/products/1405978>

| | |
|---------------------------------|--|
| Shield attenuation | 0.95 dB (f = 125 kHz) |
| | 1.64 dB (f = 500 kHz) |
| | 2.30 dB (f = 1 MHz) |
| Flame resistance | FT4 |
| Resistance to oil | yes |
| Other resistance | UV resistant |
| Special properties | UL standards PLTC and ITC |
| Ambient temperature (operation) | -30 °C ... 75 °C (cable, fixed installation) |

Environmental and real-life conditions

Ambient conditions

| | |
|---------------------------------|----------------------------------|
| Degree of protection | IP65 |
| | IP67 |
| | IP68 |
| Ambient temperature (operation) | -25 °C ... 90 °C (Plug / socket) |

SAC-5P-MR/ 2,0-924 SCO - Bus system cable



1405978

<https://www.phoenixcontact.com/us/products/1405978>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27060307 |
| ECLASS-12.0 | 27060307 |
| ECLASS-13.0 | 27060307 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC001855 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 26121600 |
|-------------|----------|

SAC-5P-MR/ 2,0-924 SCO - Bus system cable



1405978

<https://www.phoenixcontact.com/us/products/1405978>

Environmental product compliance

| | |
|------------|---|
| REACH SVHC | Diazene-1,2-dicarboxamide (C,C'-azodi(formamide)) (ADCA) 123-77-3 |
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e No hazardous substances above threshold values |

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com