

1628525

https://www.phoenixcontact.com/us/products/1628525

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



M17, Device connector front mounting, series: M17 PRO, angled rotatable, for standard and ONECLICK fast locking system, No. of pos.: 8, contact connection type: Pin, Crimp connection, flange dimensions: 28 mm x 28 mm, coding: N, Item is lead-free in accordance with RoHS II without Exemption 6c (Pb < 0.1 %)

Your advantages

- · Solutions with cross-manufacturer compatibility for standard and fast locking systems
- · Modern, consistent design for highly convenient operation
- · Crimping connection: vibration- and temperature-resistant assembly
- · All housing can be fitted with pin or socket contacts
- · Safe use in the field, thanks to high degree of protection

Commercial data

Item number	1628525
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	AB30
Product key	ABRAAM
GTIN	4055626707334
Weight per piece (including packing)	103.7 g
Weight per piece (excluding packing)	103.7 g
Customs tariff number	85366990
Country of origin	DE



1628525

https://www.phoenixcontact.com/us/products/1628525

Technical data

Notes

General	Order 8 x Ø 1 mm crimp contacts separately			
Safety note				
Safety note	WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.			
	 WARNING: Commission properly functioning products only. The products must be regularly inspected for damage. Decommission defective products immediately. Replace damaged products. Repairs are not possible. 			
	 WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product. 			
	 The products are suitable for applications in plant, controller, and electrical device engineering. 			
	 When operating the connectors in outdoor applications, they must be separately protected against environmental influences. 			
	 Assembled products may not be manipulated or improperly opened. 			
	 Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at phoenixcontact.com/products). 			
	 When using the product in direct connection with third-party manufacturers, the user is responsible. 			
	 For operating voltages > 50 V AC, conductive connector housings must be grounded 			
	 Ensure that the protective or functional ground has been properly connected. 			
	 VDE 0100/1.97 § 411.1.3.2 and DIN EN 60 204/11.98 § 14.1.3 are applicable when combining several circuits in a cable and/or connector 			
	Only use tools recommended by Phoenix Contact			
	 The installation notes/Design In documents online on the download page at phoenixcontact.com/products must be observed for this product. 			
	 Operate the connector only when it is fully plugged in and interlocked. 			
	 Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the standards. 			
	 Observe the minimum bending radius of the cable. Lay the cable without twisting it. 			
	 The connector warms up in normal operation. Depending on the ambient conditions, the surface of the connector can continue to warm up. In this case, the user is responsible for posting 			



1628525

https://www.phoenixcontact.com/us/products/1628525

uct properties	
Product type	Circular connectors (device side)
rial specifications	
Flammability rating according to UL 94	V0
nector	
ulating body	
Coding	N
nsertion/withdrawal cycles	100
Connection method	Crimp connection
Contact switching type	Pin
Application	Signal
Number of positions	8
Connection profile	8
Contact diameter Power contacts	1 mm
Rated current Power contacts	8 A
Rated voltage	60 V
Rated surge voltage	1.5 kV
Overvoltage category	III
Degree of pollution	3
nstallation height	3000 m
using	
Housing material	GD-Zn
Flange dimensions	28 mm x 28 mm
Гуре of locking	for standard and ONECLICK fast locking system
Degree of protection (plugged in)	IP67
	IP68, 24 h / 2 m



1628525

https://www.phoenixcontact.com/us/products/1628525

Classifications

UNSPSC 21.0

ECLASS

252.60				
	ECLASS-11.0	27440109		
	ECLASS-12.0	27440109		
	ECLASS-13.0	27440109		
ETIM				
	ETIM 9.0	EC003569		
UNSPSC				

39121400



1628525

https://www.phoenixcontact.com/us/products/1628525

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com