HSC-LR 9U KIT 5015 - Locking

2203851

https://www.phoenixcontact.com/us/products/2203851

DIN rail housing, 9U, Lock and Release system, width: 16.1 mm, height: 111.8 mm, depth: 8.8 mm, color: blue (similar RAL 5015)

Your advantages

- Easy, tool-free mounting
- Lock and Release interlock in contrasting color for intuitive operation
- Plastic in accordance with UL94 V0: for more rigorous flammability requirements

Commercial data

Item number	2203851
Packing unit	10 pc
Minimum order quantity	10 pc
Note	Made to order (non-returnable)
Product key	ACHCMZ
GTIN	4063151708641
Weight per piece (including packing)	5.86 g
Weight per piece (excluding packing)	5.85 g
Country of origin	DE

Technical data

Notes

General	Refer to the data sheet for the range in the download area.

Product properties

Product type	Mounting material
Housing series	ME-IO
Type	9U
Housing type	DIN rail housing

Dimensions

Width	16.1 mm
Height	111.8 mm
Depth	8.8 mm

Material specifications

Color (Housing)	blue (RAL 5015)
Flammability rating according to UL 94	V0
Surface characteristics	untreated
Housing material	Polyamide

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-40 °C ... 105 °C (depending on power dissipation)
Ambient temperature (storage/transport)	-40 °C ... 55 °C
Ambient temperature (assembly)	-5 °C ... 100 °C
Relative humidity (storage/transport)	80 %

Mounting

Mounting type	Snap in

Packaging specifications

Type of packaging	packed in cardboard
Outer packaging type	Carton

Classifications

ECLASS

ECLASS-11.0	27182702
ECLASS-13.0	27190605

ETIM

ETIM 9.0	EC001031

UNSPSC

UNSPSC 21.0	31261500

HSC-LR 9U KIT 5015 - Locking

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values