

# BLUEMARK CLED - Printer



5147999

<https://www.phoenixcontact.com/us/products/5147999>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Printers with LED-UV technology for printing plastic labels in UniCard format.



## Your advantages

- Easy and time-saving operation
- The printer detects the direction of the inserted sheets and automatically rotates printing 180° if required
- Instant wipe resistance, making the labels ready for immediate use
- Fast labeling of plastic labels for terminal, conductor, cable, and device marking applications
- Solvent-free labeling of up to 10000 markers per hour
- Environmentally-friendly high-speed printer with modern UV technology
- Automatic material feed
- Can be networked via Ethernet

## Commercial data

Item number	5147999
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	BG01
Product key	BG1211
Catalog page	Page 35 (C-3-2017)
GTIN	4046356586177
Weight per piece (including packing)	22.4 kg
Weight per piece (excluding packing)	16 kg
Customs tariff number	84433210
Country of origin	DE

## Technical data

### Product properties

Product type	Printing system
--------------	-----------------

### Marking

Identification technology	UV LED technology
---------------------------	-------------------

### Device properties

Operating system	MS Windows Vista, MS Windows 7 (32/64-bit), MS Windows 8 (32/64-bit), MS Windows 8.1 (32/64-bit), MS Windows 10 (32/64-bit), Server 2008, Server 2008 R2, Server 2012, Server 2012 R2
------------------	---

### Electrical properties

Power consumption	74 W
-------------------	------

### Supply

Supply voltage range	100 V AC ... 240 V AC 10 % (50 Hz ... 60 Hz)
----------------------	--

### Interfaces

Interface	10/100 Mbps Ethernet
Interface	USB 2.0

### Dimensions

Width	480 mm
Height	330 mm
Length	500 mm

### Material specifications

Color	gray
-------	------

### Environmental and real-life conditions

#### Ambient conditions

Ambient temperature (operation)	5 °C ... 35 °C
Permissible humidity (operation)	10 % ... 80 %

# BLUEMARK CLED - Printer

5147999

<https://www.phoenixcontact.com/us/products/5147999>



## Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e No hazardous substances above threshold values
------------	---

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)