

# TM-RIBBON 40 BK 105 - Ink ribbon

1259008

<https://www.phoenixcontact.com/us/products/1259008>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Ink ribbon, for the E-WMS... product group in combination with the THERMOMARK E.SLEEVE applicator and the WMS... and WMS-2 HF... product groups in combination with conventional roll printers, length: 300 m, roll length: 300 m, width: 40 mm, color: black

## Product description

The TM-RIBBON 40 BK 105 is a thermal transfer ink ribbon, which is suitable for automated processing with the THERMOMARK E.SLEEVE applicator in combination with the THERMOMARK E.300 (D) / 600 (D) printers and the markers from the E-WMS... product family. Alternatively, the ink ribbon can also be used without the applicator for the identification of the E-WMS material or the WMS... and WMS-2 HF... product groups

## Your advantages

- The TM-RIBBON 40 BK 105 thermal transfer ink ribbon is suitable for automated processing with the THERMOMARK E.SLEEVE applicator
- For efficient use of the entire ink ribbon, the width is optimally tailored to the E-WMS..., WMS..., and WMS-2 HF... product groups
- When combined with the right shrink sleeve, the printing is highly resistant to solvents and mechanical influences

## Commercial data

Item number	1259008
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BG02
Product key	BG1223
GTIN	4063151367978
Weight per piece (including packing)	136.6 g
Weight per piece (excluding packing)	136.6 g
Customs tariff number	96121010
Country of origin	JP

# TM-RIBBON 40 BK 105 - Ink ribbon



1259008

<https://www.phoenixcontact.com/us/products/1259008>

## Technical data

### Product properties

Product type	Ink ribbon
Scope of delivery	Ink ribbon

### Marking

Identification technology	Thermal transfer
---------------------------	------------------

### Dimensions

Width	40 mm
Length	300 m
Length of roll	300 m

### Material specifications

Color	black
Material	Polyolefin-compatible ink coating

### Environmental and real-life conditions

#### Ambient conditions

Recommended storage conditions	23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
--------------------------------	---

# TM-RIBBON 40 BK 105 - Ink ribbon

1259008

<https://www.phoenixcontact.com/us/products/1259008>



## Classifications

### ECLASS

ECLASS-11.0	19140614
ECLASS-12.0	19140614
ECLASS-13.0	19140614

### ETIM

ETIM 9.0	EC001694
----------	----------

# TM-RIBBON 40 BK 105 - Ink ribbon



1259008

<https://www.phoenixcontact.com/us/products/1259008>

## Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)