

# UM-SE-A73/N - Lateral element



2962256

<https://www.phoenixcontact.com/pc/products/2962256>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Side element, low-profile version, for 73 mm wide U-shaped cover



## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 2962256             |
| Packing unit                         | 10 pc               |
| Minimum order quantity               | 1 pc                |
| Product key                          | ACHDDA              |
| Catalog page                         | Page 762 (C-1-2013) |
| GTIN                                 | 4017918130978       |
| Weight per piece (including packing) | 8.94 g              |
| Weight per piece (excluding packing) | 8.01 g              |
| Customs tariff number                | 85369010            |
| Country of origin                    | PL                  |

# UM-SE-A73/N - Lateral element

2962256

<https://www.phoenixcontact.com/pc/products/2962256>



## Technical data

### Product properties

|                              |                               |
|------------------------------|-------------------------------|
| Product type                 | Panel mounting base side part |
| Product family               | UM ST SE                      |
| Housing series               | UM                            |
| Type                         | Lateral element               |
| Housing type                 | Press-drawn section housings  |
| Ventilation openings present | no                            |

### Material specifications

|  |                  |
|--|------------------|
| Color (Housing)                        | green (RAL 6021) |
| Flammability rating according to UL 94 | V0               |
| Housing material                       | Polyamide        |
| Surface characteristics                | untreated        |

### Environmental and real-life conditions

#### Ambient conditions

|                                 |  |
|---------------------------------|--|
| Ambient temperature (operation) | -40 °C ... 105 °C (depending on power dissipation) |
|---------------------------------|--|

# UM-SE-A73/N - Lateral element



2962256

<https://www.phoenixcontact.com/pc/products/2962256>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27182701 |
| ECLASS-13.0 | 27190602 |

### ETIM

|          |          |
|----------|----------|
| ETIM 8.0 | EC002779 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 31261500 |
|-------------|----------|

# UM-SE-A73/N - Lateral element



2962256  
<https://www.phoenixcontact.com/pc/products/2962256>

## Environmental product compliance

|   |  |
|---|--|
| EU RoHS                                 |  |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |  |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|   | No hazardous substances above the limits |
| EU REACH SVHC                           |  |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachmarktstraße 8  
D-32825 Blomberg  
+49 (0) 5235-3 00  
[info@phoenixcontact.com](mailto:info@phoenixcontact.com)