

AI-TWIN 2X 1,5 - 8 RD - Ferrule



2100006

<https://www.phoenixcontact.com/us/products/2100006>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Ferrule, sleeve length: 8 mm, color: red

Your advantages

- These special ferrules allow chain bridges to be set up with ease
- The TWIN ferrules provide a practical way of crimping two conductors in one ferrule
- Different versions of the individual TWIN ferrules can be selected for specific applications

Commercial data

Item number	2100006
Packing unit	100 pc
Minimum order quantity	100 pc
Product key	BH3413
GTIN	4067923214873
Weight per piece (including packing)	0.189 g
Weight per piece (excluding packing)	0.189 g
Country of origin	DE

AI-TWIN 2X 1,5 - 8 RD - Ferrule



2100006

<https://www.phoenixcontact.com/us/products/2100006>

Technical data

Product properties


Product type	Cable end sleeve
Conductor category	stranded conductors, class 2, 5, 6 / B, C, K, M

Connection data

Conductor connection

Conductor cross section flexible max.	1.5 mm ²
Conductor cross section AWG max.	16
Stripping length	12 mm

Dimensions

Dimensional drawing	
Sleeve length	8 mm
Maximum stripping length	12 mm
Ferrule diameter	2.3 mm
Sleeve wall thickness	0.15 mm
Insulating collar thickness	0.3 mm
Inner dimensions of the insulating collar	3.6 mm

Material specifications

Color	red
Material	CU-DHP
Flammability rating according to UL 94	HB
Coating	tin-plated (galvanic)
Components	free from silicone and halogen

Mechanical properties

Technical data

Sleeve length	8 mm
---------------	------

Environmental and real-life conditions

Ambient conditions

Permanent temperature	105 °C (-40 °C no load / 0 °C dynamic load)
Short-term temperature	120 °C

Standards and regulations

AI-TWIN 2X 1,5 - 8 RD - Ferrule



2100006

<https://www.phoenixcontact.com/us/products/2100006>

Design according to standard	DIN 46228-4, UL 486F-F
------------------------------	------------------------

AI-TWIN 2X 1,5 - 8 RD - Ferrule



2100006

<https://www.phoenixcontact.com/us/products/2100006>

Classifications

ECLASS

ECLASS-13.0	27400201
-------------	----------

AI-TWIN 2X 1,5 - 8 RD - Ferrule



2100006
<https://www.phoenixcontact.com/us/products/2100006>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com