EB 3-6 - Insertion bridge



https://www.phoenixcontact.com/us/products/0201142



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Insertion bridge, pitch: 6.2 mm, number of positions: 3, color: gray



Commercial data

Item number	0201142
Packing unit	100 pc
Minimum order quantity	100 pc
Sales key	BE19
Product key	BE1Z2X
Catalog page	Page 467 (C-1-2019)
GTIN	4017918098865
Weight per piece (including packing)	1.693 g
Weight per piece (excluding packing)	1.665 g
Customs tariff number	85366990
Country of origin	PL

EB 3-6 - Insertion bridge



https://www.phoenixcontact.com/us/products/0201142



Technical data

Product properties

Product type	Insertion bridge
Number of positions	3
Pitch	6.2 mm

Dimensions

Pitch	6.2 mm

Material specifications

Color	gray
Material	CuZn (nickel-plated)
Insulating material	PA

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-60 °C 105 °C
Ambient temperature (storage/transport)	-25 °C 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C 70 °C
Ambient temperature (actuation)	-5 °C 70 °C
Permissible humidity (storage/transport)	30 % 70 %

Mounting

Mounting type	Screw mounting
---------------	----------------

EB 3-6-Insertion bridge



https://www.phoenixcontact.com/us/products/0201142



Classifications

ECLASS

	ECLASS-11.0	27141140
	ECLASS-12.0	27141140
	ECLASS-13.0	27250303
ΕT	ТМ	

EC000489

UNSPSC

ETIM 9.0

UNSPSC 21.0	39121400

EB 3-6 - Insertion bridge



https://www.phoenixcontact.com/us/products/0201142



Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com